

CURTIS INDUSTRIES -- #83997 BRAKE CLEANER -- 6850-01-167-0678

===== Product Identification =====

Product ID:#83997 BRAKE CLEANER

MSDS Date:07/04/1986

FSC:6850

NIIN:01-167-0678

MSDS Number: BBBJL

=== Responsible Party ===

Company Name:CURTIS INDUSTRIES

Address:34999 CURTIS BLVD.

City:EASTLAKE

State:OH

ZIP:44094

Country:US

Info Phone Num:216951-2400 EXT.282

Emergency Phone Num:216951-2400 EXT.5678

C

AGE:91636

=== Contractor Identification ===

Company Name:CURTIS INDUSTRIES

Address:34999 CURTIS

Box:City:EASTLAKE

State:OH

ZIP:44094

Country:US

Phone:216951-2400 EXT. 282

CAGE:91636

===== Composition/Information on Ingredients =====

Ingred Name:PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS:127-18-4

RTECS #:KX3850000

Fraction by Wt: 50%

OSHA PEL:100 PPM

ACGIH TLV:25PPM/100,A3 STEL;94

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHL

OROETHANE) (SARA III)  
CAS:71-55-6  
RTECS #:KJ2975000  
Fraction by Wt: 47%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:350 PPM  
ACGIH TLV:350 PPM/450STEL;9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:MAY CAUSE DIZZINESS OR NARCOSIS IN  
HIGH VAPOR CONCENTRATIONS.WILL CAUSE DEFATTING OF SKIN.EFFECTS ARE  
REVER  
SIBLE.  
Explanation of Carcinogenicity:PRESENTLY NOT ON ANY LIST.  
Effects of Overexposure:LONG TERM EXPOSURE (YEARS) VAPOR MAY CAUSE  
LUNG,LIVER OR KIDNEY DAMAGE.INHALATION:DIFFICULTY IN  
BREATHING.SKIN:REDNESS.INGESTION-VOMITING.  
Medical Cond Aggravated by Exposure:HEART DISEASE.

===== First Aid Measures =====

First Aid:GIVE OXYGEN,DO NOT INDUCE VOMITING,GASTRIC LAVAGE,WASH EYES  
AND SKIN WITH WATER.

===== Fire Fighting Measures  
=====

Flash Point:NONE  
Lower Limits:NONE  
Upper Limits:NONE  
Extinguishing Media:USE WATER FOG,DRY CHEMICAL OR CARBON DIOXIDE  
Fire Fighting Procedures:AEROSOL CANS MAY RUPTURE WHEN HEATED.  
Unusual Fire/Explosion Hazard:HEATED CANS MAY BURST.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT SWEEPING COMPOUND TO SOAK UP  
MATERIAL.PUT INTO CONTAINER.DISPOSE AS HAZARDOUS WASTE.

===== Handling and Storage

=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,OR OPEN  
FLAME.STORE AT TEMPERATURES BELOW 120F.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS IF TLV LIMIT  
IS EXCEEDED.

Ventilation:LOCAL EXHAUST

Protective Gloves:NONE REQUIRED IF SPRAYING.

Eye Protection:WEAR EYE PROTECTION.

Other Protective Equipment:LONG SLEEVE AND LONG PANTS.

Work Hygienic Pract

ices:DO NOT SMOKE WHILE SPRAYING;WASH HANDS AFTER  
USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:165F-254F

Vapor Pres:100

Vapor Density:4.0

Spec Gravity:1.4

Solubility in Water:NONE

Appearance and Odor:CLEAR-SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:HIGH TEMPERATURES

Hazardous Decomposition Produ

cts:IN A FIRE FORMS PHOSGENE &  
HYDROCHLORIC ACID.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE AS HAZARDOUS WASTE IN ACCORDANCE WITH  
EPA RCRA.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.