Product ID:ACTUATING CARTRIDGE, POWER DEVICE

MSDS Date:01/01/1987

FSC:1377

NIIN:00-824-2916

MSDS Number: BBNWH === Responsible Party ===

Company Name: WALTER KIDDE/WILSON, NORTH CAROLINA 27893

Emergency Phone Num:(919) 237-7004

CAGE:EO967

=== Contractor Identification ===

Company Name: KIDDE INC WALTER KIDDE DIV AEROSPACE OPNS

Address:2500 AIRPORT DRIVE

Box:C ity:WILSON State:NC

ZIP:27893-9604

Country:US

Phone:252-237-7004

CAGE:61423

Company Name: WALTER KIDDE/WILSON, N.C. 27893

CAGE:EO967

======= Composition/Information on Ingredients ========

Ingred Name:LEAD AZIDE (SEE SUPPLEMENTAL FOR INGREDIENTS)

CAS:13424-46-9 RTECS #:OF8650000

Ingred Name:ZIRCONIUM POWDER

RTECS #:ZH7074000 ACGIH TLV:5MG/CUM

Ingred Name: POTASSIUM PERCHLORATE

CAS:7778-74-7

RTECS #:SC9700000

Ingred Name:BARIUM CHROMATE

CAS:10294-40-3 RTECS #:CQ8760000

Ingred Nam

e:LEAD SALTS OF DINITROORTHOCRESYLATE
=========== Hazards Identification ============
Effects of Overexposure:EXPLOSIVE MATERIALS, UPON DETONATION GENERATE NOXIOUS FUMES.
======================================
First Aid:INHALATION: AVOID INHALATION OF FUMES GENERATED DURING DETONATION OF THESE DEVICES. EYES/SKIN: PROTECT FROM DECOMPOSITION PRODUCTS.
======================================
Extinguish ing Media:NONE Fire Fighting Procedures:DON'T FIGHT FIRES. EVACUATE PERSONNEL TO SAFE LOCATION. Unusual Fire/Explosion Hazard:THESE UNITS CAN EXPLOSIVELY DETONATED BY FIRE/HEAT/IMPACT/ELECTRIC CURRENT/RAPID FREQUENCY ENERGY.
========= Accidental Release Measures ==========
Spill Release Procedures:CONSULT WITH THE MANUFACTURER TO RECOMMENDED DISPOSAL METHOD.
======================================
Handling and Storage Precautions:STO RE IN ACCORDANCE TO REQUIREMENTS OF CFR TITLES 27 & THE NATIONAL FIRE PROTECTION ASSOCIATIOREGULATION. AUTO-IGNITION AT 480F. Other Precautions:UNITS ARE TO BE HANDLED ONLY BY PERSONS THOROUGHLY TRAINED AND QUALIFIED TO HANDLE EXPLOSIVE DEVICES.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NOT REQUIRED DURING NORMAL OPERATION. Ventilation:ADEQUATE TO REMOVE NOXIOUS FUMES GENERATED DURING NORMAL Protective Gloves:INSULATION Eye Protectio

n:SAFETY GLASSES Other Protective Equipment: STATIC GROUNDING IS RECOMMENDED DURING HANDLING. Supplemental Safety and Health MSDS DATED: 20 MARCH 1986. ALSO CONTAINS: CARBON (FF5250100) 5MG/CUM, TITANIUM (XR2275000). ======== Physical/Chemical Properties =========== Appearance and Odor: METALLIC W/VARIOUS TYPES OF ELEC. CONNECTIONS. ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES DON'T ATTEMPT TO OPEN/REM OVE EXPLOSIVE INTERNAL COMPONENTS. Stability Condition to Avoid: EXCESSIVE HEAT/OPEN FLAME/IMPACT/ELECTRIC **CURRENTS/RF ENERGY** Hazardous Decomposition Products: SHARPNEL/OXIDES OF METAL FUELS/LEAD/TITANIUM/ZIRCONIUM

======= Disposal Considerations ===========

Waste Disposal Methods: CONSULT THE INSTITUTE OF EXPLOSIVES MAKERS, WASHINGTON, D.C. FOR ADDITIONAL INFORMATION.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.