

=====
Product Identification
=====

Product ID:189 0755,PHOTOTYPESETTING DEVL & REPL,PT-B

MSDS Date:11/04/1982

FSC:6750

NIIN:00-001-1518

Kit Part:Y

MSDS Number: BCTWB

=== Responsible Party ===

Company Name:EASTMAN KODAK

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Emergency Phone Num:716-722-5151

CAGE:5K871

=== Contractor Identification ===

Company Name:EAST

MAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 50-55%

OSHA PEL

:10 PPM
ACGIH TLV:10 PPM/15 STEL; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:1-PHENYL-3-PYRAZOLIDINONE
CAS:92-43-3
RTECS #:UQ8750000
Fraction by Wt: 5-10%

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 34-45%

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:CAUSE IRRITATION,BURNS.
Effects of Overex
posure:INH:VAP IRRIT;EYES:VAP IRRIT.LIQUID CONTCT
CAUSES BURNS;SKIN:LIQUID CONTACT CAUSES SEVERE BURNS.

=====
===== First Aid Measures =====
=====

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED
ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED
HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR BURNS GET
MED ATTN.REMOVE CON TAMINATED CLOTHING WHILE WASHING CONTMNTD AREA.

=====
===== Fire Fighting Measures ==
=====

Flash Point:NONE
Extinguishing Media:CO*2,DRY CHEM
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT
W/WATER SPRAY.
Unusual Fire/Explosion Hazard:NONE KNOWN

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:EVACUATE UNPROTECTD PERSONS.ELIM IGN
SOURCES.USE PROTECTV EQUIP.PROVIDE VENT.STOP LEAK W/O RISK.DIKE LG
SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SM SPILL IN CONTNR
PENDNG DISPOSAL;MFG RECOMM

,NEUTR LZ W/BICARBONATE & FLUSH TO SEWER
W/H*2OIAW REGS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI.STORE IN COOL, DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.AVOID CONTACT WITH ALKALIS

Other Precautions:AVOID SKIN/EYE CONTACT W/CHEMICAL PRODUCTS.WASH THOROUGHLY AFTER HANDLING.PH OF PROD:212F/>100C

Vapor Pres:16

Vapor Density:1.4

Spec Gravity:1.07

Solubility in

Water:COMPLETE

Appearance and Odor:COLORLESS LIQUID-VINEGAR ODOR.

Percent Volatiles by Volume:97%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

PER MFR AVOID ALKALIS;FLAMMABLE/OXIDIZING MATL.

Stability Condition to Avoid:UNK

Hazardous Decomposition Products:NONE KNOWN

=====
===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTNRS PENDG DISPOSAL.SHIP WASTE MATL TO NEUTRALIZ

NG/DISPOSAL FACILITY IAW DOT/EPA

REGS.HANDLE/DISPOSE OF IAW FED,STATE/LOCAL REGS;MFGR RECOMM

NEUTRLIZE W/BICARBONATE & FLUSH TO SEWER W/LG AMT H*2O IAW EXISTNG REGS & CHECKCOLOR CODE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability

for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.