

CHEMSCOPE CORP. -- CLEANING LUBRICATING COMPD ELECT, TYPE II -- 6850-00-003-1194

===== Product Identification =====

Product ID:CLEANING LUBRICATING COMPD ELECT, TYPE II

MSDS Date:05/22/1987

FSC:6850

NIIN:00-003-1194

MSDS Number: BCTXR

=== Responsible Party ===

Company Name:CHEMSCOPE CORP.

Address:3200 E. RANDOL MILL ROAD

City:ARLINGTON

ZIP:76011

Country:US

Emergency Phone Num:(817) 640-5653

CAGE:JO767

=== Contractor Identification ===

Company Name:CHEMSCOPE CO

RP

Address:3200 E RANDOL MILL RD

Box:City:ARLINGTON

State:TX

ZIP:76011-6838

Country:US

CAGE:53984

Company Name:CHEMSCOPE CORP.

Address:3200 E. RANDOL MILL ROAD

City:ARLINGTON

ZIP:76011

Country:US

CAGE:JO767

===== Composition/Information on Ingredients =====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 65%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone De

pleting Chemical:1

Ingred Name:SILICONE

RTECS #:VW1620000

Fraction by Wt: 5%

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 30%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

===== Hazards Identification =====

Effects of Overexposure:OVER-INHALATION WILL CAUSE DIZZINESS & NAUSEA.
MAY CAUSE SKIN IRRITATION. CONTACT CAN CAUSE BURNING.

=====

===== First Aid Measures =====

First Aid:FOR OVER-INHALATION, APPLY O*2 & TREAT AS FOR CHLORINATED
SOLVENT OVEREXPOSURE. FOR SKIN, WASH WITH SOAP & WATER. FOR EYES,
FLUSH WITH COLD WATER. CONSULT DOCTOR IF ANY SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:NONE

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

=====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION: USE NORMAL
PROCEDURES FOR AEROSOL DISPOSAL METHOD ACCORDING TO RULES AND
REGULATIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP OUT OF REACH OF CHILDREN. DO NOT
STORE NEAR HEAT OR OPEN FLAME. DO NOT THROW INTO INCINERATOR. TEMPS
OVER 130F MAY CAUSE BURSTING.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN: DO NOT INHALE
VAPORS/MIST. DO NOT

PUNCTURE OR INCINERATE.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL EXHAUST-DO NOT USE PRODUCT IN A CLOSED AREA FOR
LG.PER
Supplemental Safety and Health
MSDS UNDATED; ITEM IS TYPE II OF SPEC: MIL-C-83360

===== Physical/Chemical Properties =====

HCC:V2
Vapor Pres:100
Vapor Density:4.5
Spec Gravity:1.30
Evaporation Rate & Reference:6.0 (NO. REF)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR, COLORLESS, C
HLORINATED SOLVENT ODOR.
Percent Volatiles by Volume:96.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF EVAPORATE INTO THE ATMOSPHERE IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULITIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Dep
artment
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.