View NSN Online: https://aerobasegroup.es/nsn/8030-00-007-8337

CHEM SEAL CORPORATION OF AMERICA -- CS3204, CLASS A-2, MIL-S-8802D, PART A -8030-00-007-8337

Product ID:CS3204, CLASS A-2, MIL-S-8802D, PART A MSDS Date:01/01/1985 FSC:8030 NIIN:00-007-8337 Kit Part:Y **MSDS Number: BCVCY** === Responsible Party === Company Name: CHEM SEAL CORPORATION OF AMERICA Address:11120 SHERMAN WAY City:SUN VALLEY State:CA ZIP:91352-4949 Count ry:US CAGE: JO800 === Contractor Identification === Company Name: CHEM SEAL CORPORATION OF AMERICA Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US CAGE: JO800 **Company Name: FLAMEMASTER CORPORATION** Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Phone:818-982-1650 CAGE:13422

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 10%. OSHA PEL :200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:LP-32 LIQUID POLYSULFIDE POLYMER (MFR-THIOKOL CORPORATION, CHEMICAL DIVISION)

Effects of Overexposure: AVOID EYE CONTACT OR PROLONGED SKIN CONTACT.

First Aid:EYE:IMMEDIATELY FLUSH W/WATER FOR 15 MINUTES. CALL MD IF NECESSARY. SKIN:WASH THOROUGHLY W/MILD SOAP & WATER.

Flash Point:90F CC Lower Limits:7. Upper Limits:90. Extinguishing Media:STANDARD MEDIA, CO*2, ETC. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: MFG SUGGESTS NO PRECAUTIONS NECESSARY; SOLVENT WIPE-TAKING PRECAUTIONS AGAINST FIRE AND INHALATION HAZARDS.

=================== Handling and Storage

Handling and Storage Precautions: AVOID PROLONGED CONTACT.

======= Exposure Controls/Personal Protection ==========

Ventilation:MECHANICAL-YES Protective Gloves:RECOMMENDED Eye Protection:SAFETY GOGGLES REC. Other Protective Equipment:NONE Supplemental Safety and Health PART A OF A TWO PART PRODUCT. MIX RATIO BY WEUIGHT IS 100:10(A:B).KEY1:F4

HCC:F4 Boiling Pt:B.P. Text:450F Vapor Pre s:2. Vapor Density:3.1 Spec Gravity:1.42 Evaporation Rate & amp; Reference:0.02 TOLUENE Solubility in Water:NEGLIGIBLE Appearance and Odor:OFF WHITE PASTE, POLYSULFIDE ODOR. Percent Volatiles by Volume:10.

Stability Indicator/Materials to Avoid:YES SULFURIC, NITRIC, & HYDROCHLORIC ACIDS. Hazardous Decomposition Products:NONE

Waste Disposal Methods:SANITARY LA NDFILL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.