

DOW CORNING CORPORATION -- DOW CORNING #1292 LONG LIFE BEARING GREASE --
9150-00-007-9289

===== Product Identification =====

Product ID:DOW CORNING #1292 LONG LIFE BEARING GREASE

MSDS Date:12/15/1986

FSC:9150

NIIN:00-007-9289

MSDS Number: BCVDD

=== Responsible Party ===

Company Name:DOW CORNING CORPORATION

Address:3901-SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phon

e Num:517-496-5900

Emergency Phone Num:517-496-5900

Preparer's Name:JACK L. SHENEGER

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

Company Name:INLAND PACKAGING INC

Address:209 PETERSON DR

Box:644

City:ELIZABET

HTOWN
State:KY
ZIP:42701-9804
Country:US
Phone:502-737-6757
CAGE:66172

=====
Composition/Information on Ingredients
=====

Ingred Name:FLUOROPOLYSILOXANE
Fraction by Wt: 85.0%

Ingred Name:THICKING AGENT
Fraction by Wt: 15.0%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:UNKNOWN Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE:MAY IRRITATE EYES WITH SLIGHT
PAIN,REDNESS,AND POSSIBLE MINOR CORNEAL INJURY. CH
RONIC:SLIGHT SKIN
IRRITATION.

Effects of Overexposure:EYES:IRRITANT,SLIGHT PAIN,REDNESS,CORNEAL
INJURY;SKIN:SLIGHT IRRITATION ON PROLONGED CONTACT.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
First Aid Measures
=====

First Aid:WIPE OFF AND FLUSH WITH EXCESS OF WATER;CALL A PHYSICIAN IF
NECESSARY.

=====
Fire Fighting Measures
=====

Flash Point Method:OC

Flash Point:>200F/93C

Extinguishing Medi

a:WATER FOG,CO*2,DRY CHEMICAL,FOAM

Fire Fighting Procedures:SCBA AND PROTECTIVE CLOTHING SHOULD BE WORN IN
FIGHTING.

Unusual Fire/Explosion Hazard:NONE KNOWN TO DOW CORNING.

=====
Accidental Release Measures
=====

Spill Release Procedures:MOP, WIPE OR SOAK W/ABSORBENT MATL

=====
Handling and Storage
=====

Handling and Storage Precautions:USE REASONABLE CARE.KEEP THE CONTAINER
CLOSED WHEN NOT IN USE.

Other Precautions:TOXI

C VAPORS MAY BE PRODUCED ABOVE 550F. PROVIDE
ADEQUATE VENT IF USED ABOVE THIS POINT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE
VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Supplemental Safety and Health

TOXIC VAPORS

MAY BE PRODUCED ABOVE 550F.PROVIDE ADEQUATE VENTILATION IF
USED.

===== Physical/Chemical Properties =====

HCC:V6

Vapor Pres: