

TURCO PRODUCTS INC., SUB. OF PENNWALT CORP. -- TURCO 4217 -- 6850-00-014-3914

===== Product Identification =====

Product ID:TURCO 4217

MSDS Date:06/23/1986

FSC:6850

NIIN:00-014-3914

MSDS Number: BCVJC

=== Responsible Party ===

Company Name:TURCO PRODUCTS INC., SUB. OF PENNWALT CORP.

Address:24700 S. MAIN ST.

Box:6200

City:CARSON

State:CA

ZIP:90749

Country:US

Info Phone Num:213-835-1394

Emergency Phone Num:714-890-3600

Preparer's Name:C.A.EISENHARD

CAGE:61102

=

== Contractor Identification ==

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:TURCO PRODUCTS

Address:ST RD 95 WEST

Box:City:MARION

State:OH

ZIP:43302

Country:US

CAGE:95510

Company Name:TURCO PRODUCTS, INC. DIVISON OF ELF ATOCHEM NORTH AMERICA

Address:2000 MARKET ST

Box:City:PHILADELPHIA

State:PA

ZIP:19103-3222

Country:US

Phone:215-419-7890

CAGE:61102

===== Comp

osition/Information on Ingredients =====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 50.0%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

===== Hazards Identification =====

Effects of Overexposure:INHAL:HEADACHE,NOSE & THROAT
IRRIT.SKIN:IRRITATES,DEFAT.EYES:SEVERE IRRITATION.

===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR.GIVE O*2 IF BR
EATH DIFFICULT/ART
RESPIR IF BREATH STOPPED.EYES:FLUSH W/WATER FOR 15 MIN.SKIN:REMOVE
CONTAM CLOTHING.WASH SKIN W/SOAP & WATER.INGEST:DILUTE W/LGE VOL
MILK OR WAT ER.DO NOT GIVE IF UNCONSCIOUS. CONTACT DR.

===== Fire Fighting Measures =====

Flash Point:70F,21C,TCC
Lower Limits:2.5
Extinguishing Media:CO*2,WATER,CHEMICAL FOAM.
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.CONTAIN
SPILLAGE.VENTILATE AREA.WIPE UP OR ABSORB ONTO ABSORBENT
MATERIAL,RECOVER IN DRUMS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:USE CARE IN OPENING TO AVOID
SPURTING.DRUMS & METALLIC HANDLING EQUIPMENT SHOULD BE GROUND TO
AVOID STATIC CHARGING.
Other Precautions:VAPOR HEAV THAN AIR.COLLECTS IN LOW AREAS. PROVIDE
PERSONNEL W/RESPIRATORY

PROTECTION & SAFETY LINE.KEEP UNDER
OBSERVATION.EMPTY DRUMS MAY CONTAIN FLAM VAPORS.KEEP SEALED.STORE
IN FLAM AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF CONTAINED GEAR IF TLV IS EXCEEDED;SULL FACE
W/POS PRESS MODE
Ventilation:LOCAL RECOMMENDED
Protective Gloves:NEOPRENE
Eye Protection:RUBBER FRAMED GOGGLES
Other Protective Equipment:SOLVENT RESISTANT BOOTS & APRON (NEOPRENE)
Supplemental Safety and Health
MSDS DATED 6-23-8
6.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:=82.2C, 180.F
Vapor Pres:30
Vapor Density:>1.0
Spec Gravity:0.90
Evaporation Rate & Reference:>1.0(BU ACETATE)
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR LIGHT YELLOW LIQD,ALCOHOL ODOR
Percent Volatiles by Volume:50

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING & CORROSIVE MATL
Stability Condition to Avoid:
SOURCE IGN,OPEN FLAME,HEAT.
Hazardous Decomposition Products:CARBON MONOXIDE,CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:POSSIBLE METHODS 1:LANDFILL UNDER APPLICABLE
LOCAL,STATE,FED REGS.2:BURN IN CHEMICAL FURNACE W/APPROPRIATE FUME
SCRUBBING SYSTEM.3:TRANSFER TO RECLAIMING CENTER FOR SOLVENT
RECOVERY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elem

ents of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.