

ANITEC IMAGE CORPORATION -- 5202-001,REPROLITH LITHGRAPHIC CEVLPR,PART A --
6750-00-032-0617

===== Product Identification =====

Product ID:5202-001,REPROLITH LITHGRAPHIC CEVLPR,PART A

MSDS Date:01/01/1985

FSC:6750

NIIN:00-032-0617

Kit Part:Y

MSDS Number: BCVSQ

=== Responsible Party ===

Company Name:ANITEC IMAGE CORPORATION

Emergency Phone Num:(607) 774-3300

CAGE:61263

=== Contractor Identification =

==

Company Name:ANITEC IMAGE CORP

Address:40 CHARLES ST

Box:4444

City:BINGHAMTON

State:NY

ZIP:13902

Country:US

Phone:607-774-3333

CAGE:61263

===== Composition/Information on Ingredients =====

Ingred Name:HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 8.0%

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:SODIUM-POTASSIUM FORMALDEHYDE BISULFITE

Fraction by Wt: 30.0%

Ingred Name:POTASSIUM HYDROXIDE (SARA III)

CAS:

1310-58-3
RTECS #:TT2100000
Fraction by Wt: 0.5%
OSHA PEL:C, 2 MG/M3
ACGIH TLV:C 2 MG/M3; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:WATER;CAS #732-18-5 ;% WT BY DIFFERENCE
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 61.5%

===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE IRRITATION TO SKIN OR EYES.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST F
OR 15 MIN & GET MED
ATTN;SKIN:FLUSH/WASH W/PLENTY OF H*2O.IF IRRITATION OCCURS,GET MED
HELP

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG APP H*20 SPRAY TO COOL
CONTR.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. STOP LEAK. H*2O
SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEA
T. PROVIDE
VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS.
LG SPILL:DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED
AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING.
Other Precautions:PH OF PART A SOLUTION:6.665

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO

SPECIAL REQMENTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.
Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT
CONTACT.
Supplemental Safety and Health
PART A OF 2 PART KIT;GAF CORP USED ABOVE CAT# & ITEM TRNSFR TO
ANITEC;AFTER TRANSFR ANITEC CORP ASSIGND CAT #5202-015 &
DISCONTINUED FROM PRODUCTION;SEE P/N IND "B" FOR PART B;INFO RCVD

84013.KEY1:N1

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:210F
Spec Gravity:1.301
Solubility in Water:COMPLETE
Appearance and Odor:CONCENTTRATE,CLEAR,COLORLESS LIQ,PUNGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NO SPECIFIC INCOMPATIBILITY.
Stability Condition to Avoid:NONE KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person util

izing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.