

ANITEC IMAGE CORPORATION -- 5202-001,REPROLITH LITHGRAPHIC DEVLPR,PART B --
6750-00-032-0617

===== Product Identification =====

Product ID:5202-001,REPROLITH LITHGRAPHIC DEVLPR,PART B

MSDS Date:01/01/1985

FSC:6750

NIIN:00-032-0617

Kit Part:Y

MSDS Number: BCVSR

=== Responsible Party ===

Company Name:ANITEC IMAGE CORPORATION

Emergency Phone Num:(607)774-3300

CAGE:61263

=== Contractor Identification ==

=

Company Name:ANITEC IMAGE CORP

Address:40 CHARLES ST

Box:4444

City:BINGHAMTON

State:NY

ZIP:13902

Country:US

Phone:607-774-3333

CAGE:61263

===== Composition/Information on Ingredients =====

Ingred Name:POTASSIUM BROMIDE;CAS #7758-02-3

CAS:7758-02-3

RTECS #:TS7650000

Fraction by Wt: 1.10%

Ingred Name:SODIUM SULFITE;CAS #7757-83-7

CAS:7757-83-7

RTECS #:WE2150000

Fraction by Wt: 1.20%

Ingred Name:POTASSIUM CARBONATE;CAS #584-08-7

CAS:584-08-7

RTECS #:TS7750000

Fraction by Wt:

31.0%

Ingred Name:WATER;CAS #7732-18-5; % WT BY DIFFERENCE
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 66.7%

===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE SKIN OR EYES IRRITATION.

===== First Aid Measures =====

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED
ATTN;SKIN:FLUSH/WASH W/PLENTY OF H*2O.IF IRRITATION OCCURS,GET MED
HELP.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG APP H*20 SPRAY TO COOL
CONTR.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION
SOURCES. STOP LEAK. H*2O SPRAY COOL CONT/DIVERT SPILL FROM
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL
ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL
ABSORBENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED
AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING.
Other Precautions:PH OF PART B SOLUTION:11.25 PER MFR;THIS ITEM IS NOT
ANY MORE IN PRODUCTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY
CONDITIONS/ADEQUATE

VENT.
Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT.
Supplemental Safety and Health
PART B OF 2 PART KIT;ABOVE CAT WAS USED BY GAF CORP;AFTER
TRANSPR,ANITEC CORP AS SIGNED CAT #5202-015 & DISCONTINUED ITEM FM
PRODUCTION;SEE P/N"A" FOR PART A DATA;INFOR RCVD FM MFR 1/13/84
KEY1:N1

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:210F
Spec Gravity:1.338
Solubility in Water:COMPLETE
Appearance and Odor:CONCENTRATE,COLORLESS,CLEAR LIQD,MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
PER MFR,NO SPECIFIC INCOMPATIBILITY;BUT AVOID OXIDZR/FLAMM
Stability Condition to Avoid:NONE KNOWN

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek

competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.