

KRYLON DEPT.,DIV OF BORDEN CHEM.,BORDEN INC. -- 1602,FLAT BLACK,37078,SPRAY PAINT --
8010-00-054-1950

===== Product Identification =====

Product ID:1602,FLAT BLACK,37078,SPRAY PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-054-1950

MSDS Number: BCWGT

=== Responsible Party ===

Company Name:KRYLON DEPT.,DIV OF BORDEN CHEM.,BORDEN INC.

Address:630 E WASHINGTON

Box:390

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

CAGE:JO900

=== Contractor Identification ===

Company Name:KRYLON DEPT.,DIV OF BORDEN CHEM.,BORDEN INC.

Address:630 E WASHINGTON

Box:390

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

CAGE:JO900

Company Name:KRYLON PRODUCTS

Address:31500 SOLON ROAD

Box:City:SOLON

State:OH

ZIP:44139

Country:US

Phone:800-832-2541/216-566-2917

CAGE:87187

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 32%

OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (SARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 10%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 20%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX227
5000
Fraction by Wt: 18%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 4%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:LIGHTHEADEDNESS,DIZZY,HEADACHE,FATIGUE,MUSCULAR
WEAKNESS,MENTAL CONFUSION,NAUSEA,INSOMNIA

===== First Aid Meas

ures =====

First Aid:REMOVE TO FRESH AIR.IF SPRAYED IN EYES,FLUSH WITH WATER.

===== Fire Fighting Measures =====

Extinguishing Media:DRY CHEM.

Fire Fighting Procedures:NORMAL CLASS B FIRE PROCEDURES.

Unusual Fire/Explosion Hazard:IF SPRAYED WITHIN 12 IN. OF OPEN FLAME
SPRAY MAY IGNITE & BURN LIKE A BLOWTORCH

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.SOAK UP
WITH

ABSORBENT MATERIAL.VENTILATE AREA.MATERIAL NOT DANGEROUS WHEN
SOLVENTS HAVE EVAPORATED.(MFG)

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE OVER 120F.DO NOT PLACE
CAN ON RADIATOR,STOVE,DIRECT SUNLIGHT OR NEAR OTHER HEAT SOURCES.

Other Precautions:DO NOT PUNCTURE OR INCINERATE CONTAINER.DO NOT BREATH
FUMES.USE AIR PACK TO AVOID PYROLYSIS PRODUCT.

===== Exposure Controls/Personal Protection =====

=====

Respiratory Protection:VENTILATE ADEQUATELY

Ventilation:AS NEEDED TO KEEP AREA BELOW ESTIMATED TLV

Supplemental Safety and Health

CONTAINER IS UNDER INTERN PRESS OF ABOUT 60 LBS PSIG AT 70F. ADD

INGRED: METHANOL,1.0

Spec Gravity:1.0 (BU AC)

Solubility in Water:SLIGHT

Percent Volatiles by Volume:88

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:COMBUSTION MAY PRODUCE TOXIC &
IRRITATI

NG CHLORINE COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:WHEN DRY DISPOSE OF BY INCINERATION OR LANDFILL
IN ACCORDANCE WITH ALL LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate

and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.