

3M COMPANY -- CLEAR AUTO GLASS SEALER, 08551 -- 8030-00-057-4109

===== Product Identification =====

Product ID: CLEAR AUTO GLASS SEALER, 08551

MSDS Date: 04/12/1990

FSC: 8030

NIIN: 00-057-4109

MSDS Number: BCWLS

=== Responsible Party ===

Company Name: 3M COMPANY

Address: 3M CENTER

City: ST. PAUL

State: MN

ZIP: 55144-1000

Country: US

Info Phone Num: 612-733-1110

Emergency Phone Num: 612-733-5454; 800-253-3436

CAGE: 76381

=== Contractor Identification ===

Company Name: 3M MIN

NESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address: 3M CTR

Box: City: SAINT PAUL

State: MN

ZIP: 55144-1000

Country: US

Phone: 800-364-3577/651-737-6501 (24 HOURS)

CAGE: 04963

Company Name: MINNESOTA MINING AND MFG CO, DBA 3M

Address: 3M CENTER BLDG 224-5S-04

Box: City: SAINT PAUL

State: MN

ZIP: 55144-1000

Country: US

Phone: 866-556 5712 / 612-733-1110

CAGE: 76381

Company Name: STEVEN INDUSTRIES

Address: 39 AVENUE C

Box: 8

City: BAYONNE

State: NJ

ZIP: 07002-3417

Country: US

Phone: 201-437-6501

CAGE: 33150

=====

== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 11.0%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC PETROLEUM NAPHTHA (TLV IS AN ESTIMATE)  
Fraction by Wt: 44.0%  
ACGIH TLV:500 PPM (MFG)

===== Hazards Identification =====

Effects of Overexposure:MAY BE IRRIT TO EYES, SIN & UPPER RESP  
SYST.BREATHING CONC  
VAPORS MAY CAUSE NARCOSIS.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/PLENTY OF WATER. SEEK MEDICAL ATTN.SKIN:WASH  
W/SOAP & WATER. INHALATION:PROVIDE FRESH AIR.INGESTION:DO NOT  
INDUCE VOMITING. CALL A MD.

===== Fire Fighting Measures =====

Flash Point:42.0F,5.6C  
Lower Limits:1.0  
Upper Limits:7.0  
Extinguishing Media:CO\*2, FOAM, DRY CHEMICAL  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PR  
OTECTIVE  
EQUIPMENT .  
Unusual Fire/Explosion Hazard:FLAMMABLE. OVERHEATED, CLOSED CONTAINERS  
ADJACENT TO FIRE COULD EXPLODE DUE TO PRESSURE BUILDUP.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL IGNITION SOURCES,COLLECT  
SPILLED MATERIAL. CLEAN UP RESIDUE.

===== Handling and Storage =====

Handling and Storage Precautions:EXTREMELY FLAMMABLE.KEEP AWAY FROM ALL  
SOURCES OF IGNITION. US

E ONLY IN AREAS ADEQUATELY VENTILATED TO  
KEEP VAPORS BELOW TLV OF SOLVENTS.  
Other Precautions:AVOID EYE CONTACT. AVOID PROLONGED BREATHING OF  
VAPORS & PROLONGED OR REPEATED SKIN CONTACT. AVOID INGESTION.

===== Exposure Controls/Personal Protection =====

Ventilation:MFG RECM LOCAL EXHAUST  
Protective Gloves:RECOMMENDED  
Eye Protection:RECOMMENDED  
Supplemental Safety and Health  
% VOLATILE BY WEIGHT: APPROX. 55

===== Physical/Chemical Properties =====  
=====

Boiling Pt:B.P. Text:232F,111C  
Vapor Pres:25  
Vapor Density:3  
Spec Gravity:0.88 (H\*2O=1)  
Evaporation Rate & Reference:>2 (ETHER=1)  
Solubility in Water:NIL  
Appearance and Odor:CLEAR LIQUID - ODOR OF NAPHTHA  
Percent Volatiles by Volume:55

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED BY MANUFACTURER.  
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

===== Disposal Consideration  
S =====

Waste Disposal Methods:DO NOT LANDFILL. INCINERATE IF IN ACCORDANCE  
W/FED, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek comp

etent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.