Product ID:PR50-AF, TT-C-498B, COATING CMPD MSDS Date:01/01/1985 FSC:8030 NIIN:00-058-6795 MSDS Number: BCWNF === Responsible Party === Company Name: TRIRAM CORP Emergency Phone Num:617-875-6600 CAGE:59983 === Contractor Identification === Company Name: TRIRAM CORP Address:721 WAVERLY ST Box:642 City:FRAMINGHAM State:MA ZIP:01701-8512 Country:US CAGE:59983

===

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 OSHA PEL:100 PPM

Ingred Name: ALUMINUM PIGMENT, % APPROX Fraction by Wt: 11%.

Ingred Name:ASPHALT, % APPROX RTECS #:SE7350000 Fraction by Wt: 68% ACGIH TLV:5MG/CUM, FUMES

Ingred Name:ASBESTOS, CHRYSOTILE CAS:12001-29-5 RTECS #:CI6478500 Fraction by Wt: 10% OSHA PEL:0.2 FIBERS/CC ACGIH TLV:2 FIBERS/CC; A1;9192

Ingred Name:ADDITIVES Fraction by Wt:

1%
======================================
Effects of Overexposure:MFR STATES SAME AS ANY PETROLEUM DERIVATIVE
======================================
First Aid:EYE: IMMED FLUSH W/WATER AT LEAST 15 MIN, CALL MD. SKIN: WASH THOROUGHLY AFTER HANDLING.
======================================
Flash Point:124F COC Extinguishing Media:CO*2, FOAM, SAND Fire Fighting Procedures:SIMILAR TO OTHER PETROLEUM PR OD
Unusual Fire/Explosion Hazard:NONE, SIMILAR TO OTHER PETROLEUM PROD
======================================
Spill Release Procedures:DRY W/NORMAL GARAGE FLOOR CLEANER, I E SPEEDY OIL DRY. MFR SUGGESTS USING MINERAL SPIRITS OR KEROSENE ON DRIED MATL TAKING PRECAUTIONS AGAINST FIRE & INH HAZ.
======================================
Handling and Storage Precautions: AVOID EXCESSIVE HEAT OR MOISTURE
======== Exposure Contro Is/Personal Protection ====================================
Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT IF NEC Ventilation:LOCAL EXHST, YES Protective Gloves:IF NEC Eye Protection:GOGGLES IF NEC Other Protective Equipment:AS REQ Supplemental Safety and Health ADDRESS: TRIRAM CORP. 721 WAVERLY ST. FRAMINGHAM, MA 01701.
======================================

HCC:V4 Boiling Pt:B.P. Text:313F Spec Gravity:1.04 Evaporation Rate & amp; Reference:0.06 Appearance and Odor:SILVER COLOR,

## ODOR SIMILAR TO MINERAL SPIRITS

Stability Indicator/Materials to Avoid:YES WATER Stability Condition to Avoid:EXCESSIVE HEAT Hazardous Decomposition Products:NONE

Waste Disposal Methods: DISPOSE IAW LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Departme nt

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.