

THE DEXTER CORP -- EPK 0151, EPOXY PATCH KIT PART B, AB0151 -- 8040-00-059-5477

=====  
Product Identification  
=====

Product ID:EPK 0151, EPOXY PATCH KIT PART B, AB0151

MSDS Date:12/19/1988

FSC:8040

NIIN:00-059-5477

Kit Part:Y

MSDS Number: BCWPJ

=== Responsible Party ===

Company Name:THE DEXTER CORP

Address:ONE DEXTER DRIVE

City:SEABROOK

State:NH

ZIP:03874

Country:US

Info Phone Num:603-474-5541

Emer

gency Phone Num:603-926-0910

Preparer's Name:DR. SHELDON CLARK

CAGE:HO354

=== Contractor Identification ===

Company Name:DEXTER CORP DEXTER ELECTRONIC MATERIALS DIV

Address:15051 E DON JULIAN RD

Box:City:LA PUENTE

State:CA

ZIP:91746

Country:US

Phone:818-968-6511

CAGE:12405

Company Name:THE DEXTER CORP

Address:ONE E WATER ST

Box:1282

City:WAUKEGAN

State:IL

ZIP:60085

Country:US

Phone:708-623-4200

CAGE:HO354

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NO INGRE

DIENT FOR THIS FORMULATION\_INGREDIENT

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:MATERIAL IS CORROSIVE TO SKIN. MAY CAUSE CHEMICAL BURNS TO SKIN AND EYES. REPEAT CONTACT MAY CAUSE SENSITIZATION. SIGNS & SYMPTOMS OF EXPOSURE:SKIN RASH, IRRITATION; POSSIBLE BURNS.

Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:SEE HEALTH HAZARDS.

=====  
===== First Aid Measures =====

First Aid:INGEST:CALL MD IMMEDIATELY . INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O\*2/ARTF RESP) . EYES:IMMEDIATELY FLUSH W/POTABLE WATER FOR MINIMUM OF 15 MINUTES, SEEK ASSISTANCE FROM MD ( ). SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD .

=====  
===== Fire Fighting Measures =====

Flash Point  
Test Method:COC  
Flash Point:265F,129C  
Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.  
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT .  
Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASSES MAY BE LIBERATED.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP EXCESS & TRANSFER TO METAL CONTAINERS. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS, OR USE DETERGENT.  
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. FOLLOW RECOMMENDED CURING SCHEDULE.  
Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED WITH GOOD INDUSTRIAL VENTILATION; NIOSH/MSHA AP

PRVD ORGANIC RESPIRATOR.

Ventilation:LOCAL EXHST: PREFERABLE. MECH: ACCEPTABLE

Protective Gloves:RUBBER/PLASTIC

Eye Protection:ANSI APPROVED CHEM SAFETY GOGGLES

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

EMERGENCY EYE BATH AND DELUGE SHOWER .

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FILLER PARTICLES ARE THOROUGHLY WETTED BY VEHICLE SO AIRBORNE EXPOSURE  
DOES NOT OCCUR UNLESS CURED MATERIAL IS SUBSEQUENTLY GROUND,  
M

ACHINED OR SANDED. CNDTNS TO AVOID (POLYM):TO BE BONDED. FAILURE  
TO OBSERVE CAUTIONS MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE  
RELEASE OF TOXIC GASSES.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:531F,277C

Vapor Pres:1

Spec Gravity:0.98

Evaporation Rate & Reference: