CORONADO PAINT COMPANY, INC. -- PRIMER COATING, 37875 WHITE -- 8010-00-059-8822 Product ID:PRIMER COATING, 37875 WHITE MSDS Date:01/01/1985 FSC:8010 NIIN:00-059-8822 MSDS Number: BCWPR === Responsible Party === Company Name: CORONADO PAINT COMPANY, INC.

CAGE:33200

=== Contractor Identification ===

Company Name: CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812 Country:US Phone:9

04-428-6461 CAGE:33200

======= Composition/Information on Ingredients ========

Ingred Name:PIGMENTS Fraction by Wt: 52%

Ingred Name:LINSEED & ALKYD RESINS

Fraction by Wt: 26%

Ingred Name: AROMATIC & ALIPHATIC HYDROCARBONS

Fraction by Wt: 20% ACGIH TLV:100PPM

Ingred Name: LEAD NAPHTHENATE

Fraction by Wt: 0.5%

============ Hazards Identification =========================

Effects of Overexposure: SEVERE EYE IRRITATION, DRYING OF SKIN. **EXCESSIVE INHALATION CAUSES HEADACHE** 

, DIZZINESS, NAUSEA.
======================================
First Aid:EYES: FLUSH WITH WATER. SKIN: WASH WITH MILD SOAP AND WATER AND APPLY SKIN CREAM. INHALATION: REMOVE TO FRESH AIR AND CALL A PHYSICIAN. APPLY ARTIFICIAL RESPIRATION IF NECESSARY.
============ Fire Fighting Measures ============
Flash Point:90F, SETA Lower Limits:0.9 Upper Limits:7.0 Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures:TREA T AS CLASS B FIRE. Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.
======== Accidental Release Measures ==========
Spill Release Procedures:WEAR A RESPIRATOR. FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSUREO SPARKS, FIRE OR HOT METAL SURFACES.
=========== Handling and Storage ===========
Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. USE WITH ADEQUATE VENTILATI ON. AVOID PROLONGED OR PEATED CONTACT WITH SKIN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:SELF CONTAINED NIOSH APPROVED PROTECTION IF TLV IS EXCEEDED Ventilation:LOCAL EXHAUST Protective Gloves:YES Eye Protection:YES Other Protective Equipment:EYE BATH AND SAFETY SHOWER Supplemental Safety and Health
======== Physical/Chemical Properties =========
HCC:F4 Boiling Pt:B.P. Text:240F Vapor Pres:6 Vapor Density:3.7

Spe

Appearance and Odor:WHITE OPAQUE LIQUID, PETROLEUM DISTILLATE ODOR Percent Volatiles by Volume:38
========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES OR FIRE Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE
======== D

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE AND SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

c Gravity:1.35

Evaporation Rate & Day; Reference:0.7, BUAC=1

isposal Considerations ==========

Solubility in Water: VERY SLIGHT