

PACIFIC AEROSOL, INC. -- COR-ON -- 8010-00-079-3750

=====  
Product Identification  
=====

Product ID:COR-ON

MSDS Date:01/01/1985

FSC:8010

NIIN:00-079-3750

MSDS Number: BCXPY

=== Responsible Party ===

Company Name:PACIFIC AEROSOL, INC.

Emergency Phone Num:415/ 351-4860

CAGE:34451

=== Contractor Identification ===

Company Name:PACIFIC AEROSOL, INC.

CAGE:34451

=====  
Composition/Information on  
Ingredients  
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 30%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 39%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTANE

CAS:75-28-5

RTECS #:TZ4300000

Fraction by Wt: 15.5%

ACGIH TLV:1000PPM

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000  
Fraction by Wt: 15.5%  
OSHA PEL:1000 PPM  
ACGIH TLV:ASPHYXIAN; 9192

=====  
===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES AND RESPIRATORY TRACT.  
POSSIBLE HEADACHE AND DIZZINESS.

=====  
===== First Aid Measures =====

First Aid:FUMES: MOVE AFFECTED PERSON TO FRESH AIR, RESTORE BREATHING,  
GET MEDICAL AID. EYES: FLUSH THOROUGHLY WITH WATER, GET MEDICAL  
AID.

=====  
===== Fire Fighting Measures =====

Flash Point:-19C  
Lower Limits:1.0  
Upper Limits:13.0  
Extinguishing Media:CO2, DRY CHEMICAL, FOAM  
Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE IF EXPOSED  
TO EXTREMEM HEAT OR FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE SOUCES OF IGNITION -- VENTILATE  
AREA.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120F. KEEP CONTAINERS AWAY  
FROM HEAT AND OPEN FLAME.  
Other Precautions:AVOID INHALATION OF SPRAY MIST. DO NOT TAKE  
INTERNALLY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:PAINT SPRAY MASK  
Ventilation:PROVIDE VENTILATION TO KEEP VAPORS BELOW TLV'S  
Supplemental Safety and Health  
2424 MERCED STREET/ SAN LEANDRO, CALIF. 94577.

=====  
===== Physical/Chemical Proper

ties =====

HCC:V3

Boiling Pt:B.P. Text:-10F

Vapor Density:1+

Spec Gravity:0.9

Evaporation Rate & Reference:10, BUAC=1

Solubility in Water:NONE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.