

BORDEN INC., KRYLON DEPARTMENT -- KRYLON 2101 CHERRY RED -- 8010-00-079-3760

===== Product Identification =====

Product ID:KRYLON 2101 CHERRY RED

MSDS Date:01/01/1985

FSC:8010

NIIN:00-079-3760

MSDS Number: BCXRC

=== Responsible Party ===

Company Name:BORDEN INC., KRYLON DEPARTMENT

Emergency Phone Num:215-278-2400

CAGE:EO688

=== Contractor Identification ===

Company Name:BORDEN CHEMICAL CO

Address:180 E BROAD ST

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country

:US

Phone:614-225-6124

CAGE:86142

Company Name:BORDEN INC., KRYLON DEPT

Address:FORD & WASHINGTON ST

City:NORRISTOWN

State:PA

ZIP:19404

Country:US

Phone:(215) 278-2456

CAGE:EO688

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 25%

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE

CAS:74-98-6

RTECS #:TX2275000

Fraction by Wt: 15%

OSHA PE

L:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM/75 STEL; 9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 10%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM
ACGIH TLV:200 PPM/300STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:
5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:DIZZINESS,CONFUSION,WEAKNESS.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO FRESH AIR.EYES:15 MINUTE WATER FLUSH.

===== Fire Fighting Measures =====

=====

Flash Point:NONE

Lower Limits:2

Extinguishing Media:CLASS B DRY CHEMICAL EXTINGUISHER

Fire Fighting Procedures:TREAT AS SOLVENT FIRE

Unusual Fire/Explosion Hazard:SPRAY WILL IGNITE IN OPEN FLAME.DIRECT
FLAME WILL EXPLODE CONTAINER.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.SOAK UP WITH
ABSORBENT MATERIAL.VENTILATE AREA.

===== Handling and Storage =====

H

Handling and Storage Precautions:AVOID STORAGE AT TEMPERATURES OVER
120F,HEAT SOURCES

Other Precautions:DO NOT INCINERATE CONTAINERS.DO NOT PUNCTURE
CONTAINERS. DO NOT PUNCTURE CONTAINERS.DO NOT INHALE BURNING FUMES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ADEQUATE VENTILATION.

Ventilation:VENTILATE TO KEEP BELOW TLV OF INGREDIENTS.

Protective Gloves:NOT REQUIRED

Eye Protection:NOT MANDATORY

Supplemental Safety and Health

SECTIONII-CELL

OSOLVE

ACETATE-FJ4375000-3%,TLV-100PPM.BUTANOL-E0140000-2%,TLV-50PPM.METHY
LENE CHLORIDE-PL5775000-5%,TLV-200PPM

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:NA

Vapor Pres:NA

Vapor Density:>1

Spec Gravity:BUTYL ACETATE

Solubility in Water:SLIGHT

Appearance and Odor:NA

Percent Volatiles by Volume:85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition P

roducts:COMBUSTION PRODUCES TOXIC AND
IRRITATING COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods:DISCARD WHEN DRY, AS NON HAZARDOUS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for
its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.