View NSN Online: https://aerobasegroup.es/nsn/8010-00-082-2598

NORRIS PAINT CO., DIV WHITTAKER COATINGS -- PAINT, TRAFFIC & AIRFIELD MARKING - 8010-00-082-2598

Product ID:PAINT, TRAFFIC & AIRFIELD MARKING MSDS Date:01/01/1987 FSC:8010 NIIN:00-082-2598 MSDS Number: BCYBM === Responsible Party === Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS Address:1675 COMMERCIAL ST NE Box:2023 City:SALEM State:OR ZIP:97308 Country :US Info Phone Num:503-364-2277 Emergency Phone Num:503-364-2277 CAGE:33148 === Contractor Identification === Company Name: NORRIS PAINT CO., DIV WHITTAKER COATINGS Address:1675 COMMERCIAL ST NE Box:2023 City:SALEM State:OR ZIP:97308 Country:US Phone:503-364-2277 CAGE:33148

Ingred Name:ALKYD RESIN SOLUTION RTECS #:VG7110000 Fraction by Wt: 29% ACGIH TLV:400PPM

Ingred Name: ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NO

OTHERWISE REGULATED) CAS:1302-76-7 RTECS #:BD1450000 Fraction by Wt: 29% OSHA PEL:15 MG/M3 TOTAL DUST ACGIH TLV:10 MG/M3 TDUST;8990

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE) CAS:1317-65-3 RTECS #:EV9580000 Fraction by Wt: 14% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:PETROLEUM NAPTHA Fraction by Wt: 9% ACGIH TLV:375 PPM

Ingred Name:LEAD CHROMATE YELLOW PIGMENT Fraction by Wt: 3% ACGIH TLV:.015 MG/CUM

Effects of Overexposure:INHAL OF HI CONCENTR OF VAPS MAY CAUS MILD ANEST, HDACH, NAUSEA, & DIZZ, POSS UNCONCIOUS & EVN (SUPP)

First Aid:ON SKIN:THOROUGHLY WASH EXPOS AREA W/SOAP & WATER. IN EYES:FLUSH W/LG AMTS.OF WATER-GET MEDICAL ATTN. IF SWALLOWED:DO NOT INDUCE VOMITING, KEEP PERSN WARM,QUIET, & GET MEDICAL ATTN. IF BREATHED:IF AFF ECT,REMOV PERSN TO FRESH AIR.IF BREATH STOP,GIV(SU

======

Flash Point:25F TCC -4 TCC Lower Limits:1 Upper Limits:6 Extinguishing Media:DRY CHEMICAL OR ALCOHOL FOAM. Fire Fighting Procedures:USE WATER TO COOL FIRE EXPOS SURFACES & PROTCT FIRE FIGHTING Unusual Fire/Explosion Hazard:TOXIC FUMES MAY BE LIBERATED. RESPIRATING PROTECTION REQD FOR FIRE GIHTING PERSONNEL.

Spill Release Procedures: REMOVE ALL SOURCES OF IGN

Т

ITION & PROVIDE THOROUGH VENTILATION.SMALL SPILLS MAY BE PICKED UP W/ABSORBENT MATERLS.LG SPILLS SHOULD BE DIKED THEN PUMPED OR SCOOPED W/NON-SPARKINTOOLS INTO CLOS CONTNRS.RA GS & ABSORB MATRLS SHOULD BE IMMERSED IN WATER.

Handling and Storage Precautions:KEEP CONTNRS CLOSED. AVOID DIRECT HEAT,OPEN FLAME, OR SPARK SOURCES.GROUND CONTNRS WHEN POURING & LIMIT FRE FALL TO MINIMIZE STATIC CHRG BUILD UP. Ot

her Precautions: USE ONLY W/ADEQUATE VENTILATION.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NIOSH APPRVD AIR SUPPL RESPIRATIF TLV OF PRODCT EXCEEDED.

Ventilation: PROVID SUFFICIENT MECH VENT TO MAINTN EXPOSR BELOW TLV.

Protective Gloves: IMPERMEABLE

Eye Protection:SAFTY GLASSES/CHEM SPLASH

Supplemental Safety and Health

EFFECTS OVEREXPOSR:ASPHYXIATION.LIQUID-IRRIT. TO SKN.EYE CONTCT-SEVERE IRRIT, REDNESS, TEARED,BLURRED VISION.INGEST:NAUSEA ,VOMIT,DIARRHEA.

EMERG:ARTIFICIAL RESPIRATION & GET MED. ATTN.

HCC:F2 Boiling Pt:B.P. Text:250F 120C Vapor Density:4.5 Spec Gravity:1.5 Evaporation Rate & amp; Reference:BUTYL ACETATE 3.8 Solubility in Water:INSOLUBLE Appearance and Odor:YELLOW-OPAQUE LIQUID W/PETROLEUM ODOR. Percent Volatiles by Volume:46

Stability Indicator/Materials to Avoid:YES STRON

## G OXIDANTS, ACIDS & BASES. Stability Condition to Avoid:HIGH TEMPS OR DIRECT HEATING Hazardous Decomposition Products:CO\*2, CO & POSSIBLY ACROLEIN GAS

Waste Disposal Methods:WASTE MUST BE DISPOSED OF ACCORDING TO HAZARDOUS WASTE LAWS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.