

BALTIMORE PAINT DIV OF THE SHERWIN-WILLIAMS CO -- A-593 -- 8010-00-082-2598

=====
Product Identification
=====

Product ID:A-593

MSDS Date:01/01/1985

FSC:8010

NIIN:00-082-2598

MSDS Number: BCYBP

=== Responsible Party ===

Company Name:BALTIMORE PAINT DIV OF THE SHERWIN-WILLIAMS CO

Address:1370 ONTARIO ST

City:CLEVELAND

State:OH

ZIP:44113-1701

Country:US

Emergency Phone Num:301-837-3030

CAGE:85321

==

= Contractor Identification ===

Company Name:BALTIMORE PAINT DIV OF THE SHERWIN-WILLIAMS CO

Address:1370 ONTARIO ST

City:CLEVELAND

State:OH

ZIP:44113-1701

Country:US

CAGE:85321

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 13.5%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:ALIPHATIC HYDROCARBONS

Fraction b

y Wt: 26.5%
ACGIH TLV:500 PPM

Ingred Name:ALKYD RESIN SOLIDS
Fraction by Wt: 18.7%

Ingred Name:ADDITIVES
Fraction by Wt: .3%

=====
===== Hazards Identification =====

Effects of Overexposure:IRRIT. TO EYES NOSE,THROAT, SKIN; PROLONGE
EXPOSURE MAY RESULT IN LEAD POISONING

=====
===== First Aid Measures =====

First Aid:REMOVE VICTIM TO FRESH AIR;FLUSH SKIN WITH WATER; FLUSH EYES
FOR 15 MIN. CONSULT DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point:10F,-12.2C TOC
Lower Limits:1.1
Upper Limits:8.0
Extinguishing Media:CO*2, DRY CHEM.
Unusual Fire/Explosion Hazard:SOLVENT PORTION MAY FLOAT ON WATER
CAUSING SPREAD OF FLAME

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION;ABSORB PAINT
WITH ABSORBENT AND DEPOSIT IN CLOSED CONTAINER

=====
===== Handling and Storage =====
=

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, OPEN
FLAME;AVOID CONTACT WITH SKIN, EYES,CLOTHING
Other Precautions:GROUND ALL CONTAINERS WHEN POURING

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:CARTRIDGE TYPE RESPIRATOR
Ventilation:LOCAL/MECHANICAL
Protective Gloves:SOLVENT RESISTA
Eye Protection:SAFETY GLASSES/EYE SHIELD
Other Protective Equipment:COVERALLS,APRON
Supplemental Safety and Health

=====
===== Physical/C

hemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:142F,61.1C

Vapor Pres:12

Vapor Density:2.3

Spec Gravity:1.4

Evaporation Rate & Reference:3.3 >BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:YELLOW LIQUID,HYDROCARBON ODOR

Percent Volatiles by Volume:51.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HIGH HEAT

Hazardous Decomposition Produ

cts:LEAD VAPORS

===== Disposal Considerations =====

Waste Disposal Methods:SANITARY LANDFILL

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.