

AMERON INDUSTRIAL COATINGS DIVISION -- GRAY 26492, 745-654, TT-E-529C, COMP.L --  
8010-00-087-0109

===== Product Identification =====

Product ID:GRAY 26492, 745-654, TT-E-529C, COMP.L

MSDS Date:01/01/1985

FSC:8010

NIIN:00-087-0109

MSDS Number: BCYHS

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

RTECS #:SE7550000

Fraction by Wt: 36%

ACGIH TLV:500PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR  
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 0.24%

OSHA PEL:0

.05 MG/M3 (PB)  
ACGIH TLV:0.05MG/M3(CR)A2;8990

===== Hazards Identification =====

Effects of Overexposure:INHALATION: ANESTHETIC, IRRITATION OR  
RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER  
WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH  
AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

=====  
===== Fire Fighting Measures =====

Flash Point:85T, T.C.C.  
Lower Limits:1.1  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL; POLYMER FOAM FOR  
LARGE FIRES  
Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE  
AVAILABLE  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE DUE TO PRESSURE BUILD-UP.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IG  
NITION. AVOID  
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH ERT ABSORBENT AND  
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NA  
CLASS ONE FLAMMABLE LIQUIDS.  
Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED  
WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.  
DO T FLAME

CUT, WELD OR BRAZE W/OUT APPROVED RESPIRATORS, VENTIL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: MECHANICAL FILTER, CHEMICAL-MECHANICAL FILTER  
TYPE RESPIRATOR

Ventilation: GENERAL DILUTION OR LOCAL EXHAUST

Protective Gloves: REQUIRED

Eye Protection: SPLASH-PROOF EYEWEAR

Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING.

Supplemental Safety and Health

604 E. 13TH STREET/ ANDOVER, KANSAS 67002.

=====

=== Physical/Chemical Properties =====

HCC: F3

Boiling Pt: B.P. Text: 311-373F

Vapor Density: >AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 59

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRES, HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND

FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT  
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice

e to verify and  
assume responsibility for the suitability of this information to their  
particular situation.