

===== Product Identification =====

Product ID:HEPTANE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-097-4159

MSDS Number: BCYNF

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION

Address:PARIS BYPASS

Box:M

City:PARIS

State:KY

ZIP:40361

Country:US

Info Phone Num:314-982-5000

Emergency Phone Num:314-982-5000

CAGE:62910

=== Contractor Identification ===

Company Name

:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

===== Composition/Information on Ingredients =====

Ingred Name:N-HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Fraction by Wt: >99%

OSHA PEL:500 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9293

===== Hazards Identification =====

Effects of Overexposure:INH:MAY IRRIT RESP TRACT.CAUSES

HEADACHE,DIZZ,NAUSEA

;ING:SYMP LIKE INH;SKIN/EYES:VAP/LIQ IRRITANT.

===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR.IF NEEDED,GIVE CPR/OXYGEN.GET MD;INGEST:GIVE SEVRL GL OF WATER.DO NOT INDUCE VOMITG.IMMED GET MD;SKIN:FLUSH W/LG QTY OF H*2O FOR 15 MIN.REMV CONTMNTD CLOTHES.GET MD;EYES:IMMED F LUSH W/PLENTY OF H*2O FOR AT LEAST 15 MIN.GET MD.

===== Fire Fighting Measures =====

Flash Point Method:CC
Flash Point:=-3.
7C, 25.F
Autoignition Temp:=-215.C, 419.F
Lower Limits:1.05
Upper Limits:6.7
Extinguishing Media:DRY CHEMICALS,FOAM,CO*2;WATER SPRAY TO KEEP EXPD CANS COOL
Fire Fighting Procedures:USE H*2O TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG.
Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE EXPLOSIVE.A DANGEROUS EXPLOSION HAZARD WHEN HEATED.

===== Accidental Release Measures =====

Spill Release Procedures:RMV IGN SOURCES.VENT AREA.USE RES P PROTCTION & PROTCTV CLOTHG.KEEP OUT OF SURF H*2O,SEWRS/CONFND AREAS;SM SPILL:ABSORB W/PAPER TOWELS.EVAP UNDER FUME HOOD THEN BURN CAREFULLY;LG SPILL:DIKE AREA.CONTAI N & RECOVER SPILL IF POSS;SHOVL RESDUE INTO DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:PROTCT AGAINST PHYSICAL DAMAGE.STORE IN COOL,DRY WELL VNTLTD AREA AWAY FM IGN/HEAT SOURCES,OXIDZG MATL.OUTSIDE OR DETACHED STORAGE IS PREFERRED.
Other Precautions:KEEP AWAY FROM HEAT,SPARKS,FLAMES.KEEP CONTNRS CLOSED.USE W/ADEQUATE VENT.AVOID BRTHG VAPS.WASH THOROUGHLY AFTER HNDLG.BOND/GROUND CONTNRS WHEN TRNSFRG MATERL.USE NON-SPARKG TYPE TOOL & EQUIP.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FULL FACE RESPIRATOR
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SH

OWER,EYE
WASH STATION
Supplemental Safety and Health
MSDS FROM MFR DATED 30 JUL, 85 CONFORMS TO OSHA HAZ COMM STD.

===== Physical/Chemical Properties =====

HCC:F2
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:=98.3C, 209.F
Vapor Pres:40
Vapor Density:3.5
Spec Gravity:0.683
Appearance and Odor:COLORLESS LIQ.MILD GASOLINE-LIKE ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:CO, CO*2 WHEN HEATED TO DECOMPOSITION

===== Disposal Considerations =====

Waste Disposal Methods:LG SPILL & LOT SIZES OF HAZ WASTE CAN BE
ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A
RCRA APPROVED LAND FILL FACILITY.DO NOT FLUSH TO SEWER.ENSURE
COMPLIANCE W/FED,STATE & LOCAL R EGS; REPORTABLE QTY (RQ)
(CWA/CERCLA): NOT KNOWN

Disclaimer (pro
vided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.