

ELECTROFILM MFG CO -- LUBEOLOK 4396-DILUTED -- 9150-00-101-5084

=====
Product Identification
=====

Product ID:LUBEOLOK 4396-DILUTED

MSDS Date:01/01/1985

FSC:9150

NIIN:00-101-5084

MSDS Number: BCYPY

=== Responsible Party ===

Company Name:ELECTROFILM MFG CO

Address:27727 AVE SCOTT

Box:55669

City:VALENCIA

State:CA

ZIP:91355

Country:US

Info Phone Num:805-257-2242

Emergency Phone Num:805-257-2242

CAGE:

85932

=== Contractor Identification ===

Company Name:ELECTROFILM MFG CO

Address:27727 AVE SCOTT

Box:55669

City:VALENCIA

State:CA

ZIP:91355

Country:US

Phone:805-257-2242

CAGE:85932

=====
Composition/Information on Ingredients
=====

Ingred Name:GRAPHITE (NATURAL)

RTECS #:VV7780000

ACGIH TLV:15MPPCF

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS:123-91-1

RTECS #:JG8225000

OSHA PEL:S, 100 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred

Name:KETONE (TYPE NOT SPECIFIED)

Ingred Name:ALCOHOL (TYPE NOT SPECIFIED)

Ingred Name:MOLYBDENUM DISULFIDE

CAS:1317-33-5

RTECS #:QA4697000

OSHA PEL:10 MG/M3 TDUST (MO)

ACGIH TLV:10 MG/M3 (MO); 8990

==== Hazards Identification =====

Effects of Overexposure:EYE:IRRIT.VAPORS: IRRIT
NASO-PHARYNX,HEADACHE,DROWSINESS,NAUSEA AND VOMITING.

==== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN,CONSULT DR.IN
HALATION:REMOVE TO
FRESH AIR.

==== Fire Fighting Measures =====

Flash Point:38F/+3C (TCC)
Lower Limits:1.8
Upper Limits:10
Extinguishing Media:FOAM OR POWDER

==== Accidental Release Measures =====

Spill Release Procedures:FLUSH WITH WATER TO WELL VENTILATED AREA

==== Handling and Storage =====

Handling and Storage Precautions:DO NOT FREEZE OR STORE ABOVE 120F.

==== Exposure Co
ntrols/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Supplemental Safety and Health
ADD INGRED: PHENOLIC RESIN 15%

==== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:177F/80C
Vapor Pres:70
Vapor Density:2.4
Spec Gravity:1.25
Evaporation Rate & Reference:3.5 (ETHYL ETHER)
Solubilit

y in Water:NEGLIGIBLE
Appearance and Odor:GRAY BLACK
Percent Volatiles by Volume:70

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:SOLVENT CAN FORM PEPOXIDES IF OVER
HEATED,WILL IGNITE @ 356F

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the comp
iling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.