Product ID:MIL-L-21260C GRADE 10,LUBRICATING OIL MSDS Date:04/02/1990 FSC:9150 NIIN:00-111-3199 **MSDS Number: BCZBZ** === Responsible Party === Company Name: DELTA PETROLEUM CO., INC Box:10397 **City: JEFFERSON** State:LA ZIP:70181-0397 Country:US Info Phone Num:504-833-2861 Emergency Phone Num:504-833-2861, 303-289-4483 Preparer's Name: J.R. SWOAP CA GE:7A348 === Contractor Identification === Company Name: DELTA PETROLEUM CO., INC Address:10352 RIVER ROAD, Box:10397 City:ST. ROSE State:LA ZIP:70087 Country:US Phone:504-832-2732 CAGE:7A348

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 90-95% Other REC Limits:NONE SPECIFIED ACGIH TLV:5 MG/M3 (OIL MIST)

Ingred Name: ADDITIVE PACKAGE CONTAI

NING SULPHUR, PHOSPHOROUS, CALCIUM. Fraction by Wt: 5-10% Other REC Limits:NONE SPECIFIED

======================================
Effects of Overexposure:EYES/SKIN:SLIGHT IRRIT;INHAL:MAY IRRIT RESP TRACT IF ABOVE TLV;INGEST:DIARRHEA,UPSET STOMACH.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTEN TION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.
======================================
<ul> <li>Flash Point:400F/204.4C(COC)</li> <li>Extinguishing Media:WATER SPRAY, DRY CHEM, OR CO*2;WATER/FOAM CAUSE FROTHING.</li> <li>Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY. CONTAIN RUNOFF.</li> <li>Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIR</li> <li>E MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.</li> </ul>
======================================
Spill Release Procedures: ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL: ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.
======================================
<ul> <li>Handling and Storage Precautions:STORE</li> <li>IN COOL,DRY,WELL VENTILATED</li> <li>AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED</li> <li>Other Precautions:AVOID SKIN/CLOTHG CONTACT.LAUNDER CONTAMINATED</li> <li>CLOTHES BEFORE REUSE.PER MFR,USED MOTOR OILS WERE SHOWN TO CAUSE SKIN CANCER WHEN REPEATEDLY APPLD TO MICE W/O RMVG PRVSLY APPLD MATL.WASH COMLTL</li> </ul>
======================================
Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:NORMAL ROOM VENTILA

TION.

Protective Gloves:IMPERVIOUS Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS. Supplemental Safety and Health MSDS FROM DELTA PETROLEUM EFFECTIVE:11/1/85; SPEC REF: MIL-L-21260C,GRADE 10,MILITARY SYMBOL PE 10-1 (TYPE 1)

HCC:V6 Spec Gravity:0.8762 Solubility in Water:NEGLIGIBLE Appearance and Odor:BRIGHT & CLEAR OIL, MINERAL OIL ODOR

====== Stability

and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:WHEN INVOLVD IN COMBUSTION,EMITS OXIDES OF C,N,ALDEHYD/KETON

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATI ONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular s ituation.