View NSN Online: https://aerobasegroup.es/nsn/9150-00-111-3199 ASHLAND OIL CO. -- TECTYL 873-SAE 10 -- 9150-00-111-3199 ============= Product Identification ======================== Product ID:TECTYL 873-SAE 10 MSDS Date:01/01/1987 FSC:9150 NIIN:00-111-3199 MSDS Number: BCZCB === Responsible Party === Company Name: ASHLAND OIL CO. Emergency Phone Num:606-324-1133 CAGE:81355 === Contractor Identification === Company Name: ASHLAND INC Address:1409 WINCHESTER AVE Box:391 City: ASHLAND State: KY ZIP:41114 Country:US Phone:800-622-6846 CAGE:81355 ======= Composition/Information on Ingredients ======== Ingred Name:PETROLEUM LUBE OIL Fraction by Wt: >75% ACGIH TLV:5 MG/CUM ========= Hazards Identification =============== Effects of Overexposure: EYE & SKIN: IRRIT. INHAL: IRRIT OF NASAL & RESPIR PASSAGES.INGEST:GI IRRIT, NAUSEA, VOMIT, DIARRHEA. First Aid:SKIN:WASH W/ SOAP & WATER.EYE

WATER,LIFTING LIDS OCCASIONALLY,GET MED ATTN.INHAL:REMOVE TO FRESH AIR.INGEST:DRINK WATER.INDUCE VOMIT.NEVER GIVE ANYTHING BY MOUTH TO AN UNCONS CIOUS PERSON.GET MEDICAL ATTENTION.
======================================
Flash Point:460F,238C OC Extinguishing Media:FOAM,CO*2,DRY CHEMICAL Fire Fighting Procedures:WEAR SCBA W/ FULL FACEPIECE.WATER OR FOAM MAY FROTH. Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING
TORCH ON OR NEAR DRUM(EVEN EMPTY)PRODUCT CAN IGNITE EXPLOSIVELY.
========= Accidental Release Measures ==========
Spill Release Procedures:SMALL:ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL.LARGE SPILL:REQUIRE PROTECTIVE EQUIPM.STOP SPILL AT SOURCE,DIKE AREA TO PREVENT SPREADING,PUMP LIQ TO SALVAGE TANK. REMAINING LIQ MAY BE TAKEN UP ON ABSORBMAT.SUPP
======================================
H andling and Storage Precautions:CONTAINERS OF THIS MAT MAY BE HAZARDOUS WHEN EMPTIED,SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES. Other Precautions:NONE
====== Exposure Controls/Personal Protection =======
Respiratory Protection:NIOSH/MSHA APPROVD RESPIRATOR IF TLV EXCEEDED Ventilation:LOCAL OR MECHANICAL EXHAUST Protective Gloves:NEOPRENE Eye Protection:SAFETY GLASSES Other Protective Equipment:NORMAL WORK CLOTH COVERING ARMS & LEGS. Supplemental Safety and Health MSDS PREP:OCT,83.LARGE SPILL AFTER USING ABSORBENT MATERIAL,SHOVEL INTO CONTAINERS.SPEC/STD DATA:10W GRADE AND 1 TYPE.
======== Physical/Chemical Properties =========
HCC:V6 Boiling Pt:B.P. Text:>425F,>218C Vapor Density:>1 Spec Gravity:0.892 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:NEGLIGIBLE
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES AVOID CONTACT W/ STRONG OXIDIZING A

:FLUSH W/ LARGE AMOUNTS OF

GENTS.

====== Disposal Considerations ==========

Waste Disposal Methods:SMALL:DISPOSE IN ACCORDANCE W/ LOCAL,STATE & FED REGULATIONS.LARGE SPILL:DESTROY BY INCINERATION IN ACCORD W/ APPLICABLE REGULATIONS.CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE W/ LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of D

efense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.