

ASHLAND OIL CO. -- TECTYL 873-SAE 10 -- 9150-00-111-3199

===== Product Identification =====

Product ID:TECTYL 873-SAE 10

MSDS Date:01/01/1987

FSC:9150

NIIN:00-111-3199

MSDS Number: BCZCB

=== Responsible Party ===

Company Name:ASHLAND OIL CO.

Emergency Phone Num:606-324-1133

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Country:US

Phone:800-622-6846

CAGE:81355

=====

==== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM LUBE OIL

Fraction by Wt: >75%

ACGIH TLV:5 MG/CUM

===== Hazards Identification =====

Effects of Overexposure:EYE & SKIN:IRRIT.INHAL:IRRIT OF NASAL & RESPIR
PASSAGES.INGEST:GI IRRIT,NAUSEA,VOMIT,DIARRHEA.

===== First Aid Measures =====

First Aid:SKIN:WASH W/ SOAP & WATER.EYE:FLUSH W/ LARGE AMOUNTS OF
WATER,LIFTING LIDS OCCASIONALLY,G
ET MED ATTN.INHAL:REMOVE TO FRESH
AIR.INGEST:DRINK WATER.INDUCE VOMIT.NEVER GIVE ANYTHING BY MOUTH TO
AN UNCONSCIOUS PERSON.GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:460F,238C OC

Extinguishing Media:FOAM,CO*2,DRY CHEMICAL

Fire Fighting Procedures:WEAR SCBA W/ FULL FACEPIECE.WATER OR FOAM MAY
FROTH.

Unusual Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR
NEAR DRUM(EVEN EMPTY)PRODUCT CAN IGNITE EXPLOSIV

ELY.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL:ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR
ABSORBENT OR OTHER ABSORBENT MATERIAL.LARGE SPILL:REQUIRE
PROTECTIVE EQUIPM.STOP SPILL AT SOURCE,DIKE AREA TO PREVENT
SPREADING,PUMP LIQ TO SALVAGE TANK. REMAINING LIQ MAY BE TAKEN UP
ON ABSORBMAT.SUPP

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF THIS MAT MAY BE

HAZARDOUS WHEN EMPTIED,SINCE EMPTIED CONTAINERS RETAIN PRODUCT
RESIDUES.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVD RESPIRATOR IF TLV EXCEEDED

Ventilation:LOCAL OR MECHANICAL EXHAUST

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NORMAL WORK CLOTH COVERING ARMS & LEGS.

Supplemental Safety and Health

MSDS PREP:OCT,83.LARGE SPILL AFTER USING ABSORBENT MATERIAL,SHOV
EL INTO

CONTAINERS.SPEC/STD DATA:10W GRADE AND 1 TYPE.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>425F,>218C

Vapor Density:>1

Spec Gravity:0.892

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:NEGLIGIBLE

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT W/ STRONG OXIDIZING AGENTS.

===== Disposal Considerations =====

=====

Waste Disposal Methods:SMALL:DISPOSE IN ACCORDANCE W/ LOCAL,STATE & FED
REGULATIONS.LARGE SPILL:DESTROY BY INCINERATION IN ACCORD W/
APPLICABLE REGULATIONS.CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A
LANDFILL IN ACCORDANCE W/ LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.