VARFLEX CORPORATION SUNTHOLVAR SHH 5970-00-130-2627 ===================================
Product ID:SUNTHOLVAR SHH MSDS Date:01/01/1987 FSC:5970 NIIN:00-130-2627 MSDS Number: BCZYX === Responsible Party === Company Name:VARFLEX CORPORATION Emergency Phone Num:(315) 336-4400 CAGE:79074 === Contractor Identification === Company Name:VARFLEX CORPORATION Address:512 WEST COURT STREET Box:City:ROME State:NY ZIP:13440 Country:US Phone:315-336-4400 CAGE:79074
== ====== Composition/Information on Ingredients ========
Ingred Name:PLASTICIZED POLYVINYL CHLORIDE RESIN
Ingred Name:ADDITIVES(TYPE NO SPECIFIED) Fraction by Wt: 0.5%
=========== Hazards Identification ===========
Effects of Overexposure:NONE STATED BY MFR (NONE NEEDED TO LIST)
======================================
First Aid:NONE NEEDED/NONE STATED BY MFR.
======================================

Fid511 FUIII.INOINE Fid511 FUIII.INOINE
Extinguishing Media:WATER
Fire Fighting Procedures: IN FIRES, USE APPRVD SCBA. USE WATER FOG TO
REDUCE DENSE SMOKE
Unusual Fire/Explosion Hazard:AT/ABOVE 550F,EMITS HCL GAS DURING
COMBUSTION
A L (al. D. l M
======================================
Spill Release Procedures:COLLECT PIECES OF OR UNUSED INSULATION & PLACE
IN CONTAINER FOR DISPOSAL
IN CONTAINER FOR DISTOSAL
======================================
Handling and Storage Precautions:STORE OUT OF
DIRECT SUNLIGHT & BELOW
70F.
Other Precautions:WASH & SHOWER AT THE END OF WORKDAY.
Cities i residuations. When a cities well the end of work bitts.
====== Exposure Controls/Personal Protection =======
Respiratory Protection: NONE SHOULD BE NEEDED
Ventilation:NORMAL ROOM VENTILATION.
Protective Gloves:NONE
Eye Protection:NONE
Other Protective Equipment:NONE
Supplemental Safety and Health
MSDS FROM VARFLEX CORPORATION DATED:10/85; SPEC REF:MIL-I-631D;MFR P/N
"SYNTHOLVAR SHH" I/A/W QPL-631-65 FOR TYPE F,FORM U,SUBFORM
UA,GRADE C,CLA
SS 1, CATAGORY 1,OF MIL-I-631D.
Dhysical/Chemical Dranortics
======================================
HCC:N1
Spec Gravity:1.30
Solubility in Water:NEGLIGIBLE
Appearance and Odor:WHITE FLEXIBLE SYNTHETIC RESIN.VERY MILD ODOR
Appearance and Odor.White Flexible Stitthetic Resilv.vert wild ODOR
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:EXCESSIVE HEAT OVER 400F
Hazardous Decomposition Products:COMBUSTION WILL PRODUCE HCL GAS
Tazardodo 2000mpodition i roddoto.00m200 more Wille i No200E mor 0/10
======= Disposal Consid

Flash Point:NONE

erations =========

Waste Disposal Methods: COMPLY WITH APPLICABLE LOCAL, STATE & FEDERAL LAWS & REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.