

SHELL OIL COMPANY -- 54735,TORNUS OIL 40 -- 9150-00-135-2634

=====  
Product Identification  
=====

Product ID:54735,TORNUS OIL 40

MSDS Date:01/01/1987

FSC:9150

NIIN:00-135-2634

MSDS Number: BDBFX

=== Responsible Party ===

Company Name:SHELL OIL COMPANY

Emergency Phone Num:713-473-9461

CAGE:54527

=== Contractor Identification ===

Company Name:SHELL OIL COMPANY

Box:2463

City:HOUSTON

State:TX

ZIP:77210

Country:US

Phone:800-231-6950

CAGE:54527

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBONS

Fraction by Wt: 90%

ACGIH TLV:5 MG/CUM(MIST)

Ingred Name:ADDITIVES(CONTAINING CA,N,S)

Fraction by Wt: 10%

=====  
Hazards Identification  
=====

Effects of Overexposure:VAPORS/MIST IRRITATS

RESPIRTRACT,DIZYNES,NAUS.PROLONGED/REPEATED CONTACT-DERM,OIL  
ACNE,FOLICULITIS.

=====  
First Aid Measure  
=====

S =====

First Aid:SKIN:WASH W.SOAP & H\*2O. EYES:FLUSH W. H\*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:430F/221C PMCC  
Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.  
Fire Fighting Procedures:WEAR CHEM PROT. SUIT WITH SCBA. COOL CONT  
RS  
WITH H\*2O.  
Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*2O SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL ABSORBENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====  
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.  
Other Precautions:WASH W.SOAP & WATER AFTER HANDLING.PROPERLY DISPOSE OF CONTAMINATED ARTICLES,LEATHER(INCLUDING SHOES) THAT CANNOT BE DECONTAMINATED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA/MESA APPROVD SCBA,AIR SUPPLD RESPIR.  
Ventilation:L  
OCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES/GOGGLES.  
Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6  
Spec Gravity:0.90  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:BLACK OIL,HYDROCARBON ODOR.  
Percent Volatiles by Volume:UNK

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: HIGH TEMPERATURES, IGNITION SOURCES MIST FORMING.

Hazardous Decomposition Products: MAY FORM TOXIC MATL. CO\*2, CO, VARIOUS HYDROCARBONS, ETC.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer

(provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.