

DEFT CHEMICAL COATINGS -- 02-Y-24 CTLST,YELLOW,EPOXY POLYAMIDE PRIMER --  
8010-00-142-9279

===== Product Identification =====

Product ID:02-Y-24 CTLST,YELLOW,EPOXY POLYAMIDE PRIMER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-142-9279

Kit Part:Y

MSDS Number: BDBSZ

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Emergency Phone Num:NONE

CAGE:EO418

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ALCOHOL (SARA III)

CAS:71-36-3

RTECS #:EO1400000

Fraction by Wt: 20.0%

OSHA PEL:100 PPM

ACGIH TLV:S, C 50 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effec

ts of Overexposure:EYES:MODERATE IRRIT;SKIN:POSSIBLE IRRIT BY  
SOLVENTS;INH:SOLVENT VAPORS CAN CAUSE IRRIT OR NARCOSIS

===== First Aid Measures =====

First Aid:SKIN:WIPE OFF WITH A RAG THEN THOROUGH RINSING W/H\*2O &  
WASHING W/MILD SOAP AND WATER;EYES:FLUSH W/WATER FOR AT LEAST 10  
MIN & CONSULT AN EYE PHYSICIAN;INH:REMOVE TO FRESH AIR.GIVE  
CPR/OXYGEN IF NEEDED.

===== Fire Fighting Measures =====

Flash Point  
t:20F(-6.6C)-TOC  
Lower Limits:1.7  
Extinguishing Media:CO\*2,DRY CHEM,FOAM  
Fire Fighting Procedures:DO NOT USE H\*2O STREAM ON FIRE.H\*2O SPRAY/FOG  
IS MORE EFFECTIVE  
Unusual Fire/Explosion Hazard:CAUTION AGAINST APPLICATION TO HOT  
SURFACES & USE IN AREAS WHERE SOURCES OF IGNITION MAY BE PRESENT.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN  
SOURCES.USE SAFETY EQUIP.VENTILATE AREA.STOP LEAK W/O RISK.ABSORB  
SM  
SPILL W/OIL ABSORBING COMPD/RAGS;DIKE LG SPILL.PUMP LIQ TO SALVAGE  
TANK.SHOVEL UP RESIDUE INTO COVERED DRUMS;PER MFR,FLUSH AREA W/LG  
AMOUNT OF H\*2O.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTILATED,LOW  
FIRE RISK AREA.KEEP CONTNRS TIGHTLY CLOSED.KEEP AWAY FROM HEAT,SPARK  
OR OPEN FLAME.  
Other Precautions:AVOID PROLONGED INHALATION OF VAP.PER MFR,WATER SPRAY  
OR FOG CAN BE USED EFFECTIVELY ON FIRE  
AND TO COOL HEAT/FIRE  
EXPOSED CONTNRS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:GOOD VENTILATION IS NEEDED HOWEVER USE NIOSH  
APPROVED SCBA FOR PAINTS.  
Ventilation:USE ADEQUATE VENTILATION USING EXHAUST FAN.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY/CHEM GOGGLES.  
Other Protective Equipment:AS REQD TO PREVENT PROLONGED OR REPEATED  
CONTACT.  
Supplemental Safety and Health  
TWO PART KIT. THIS IS CATALYST. SEE P/N IND "A" FOR BAS

E; ALSO SEE

P/N IND "B" FOR OTHER HAZ INGREDIENTS; MIL SPEC REFERENCE:

MIL-P-23377D, TYPE 1. KEY1:J1.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-331F

Vapor Density:>1.0

Spec Gravity:0.8484

Evaporation Rate & Reference: