

DESOTO, INC. -- 513 X 366 PRIMER; MIL-P-23377D TYPE I -- 8010-00-142-9279

=====
Product Identification
=====

Product ID:513 X 366 PRIMER; MIL-P-23377D TYPE I

MSDS Date:01/01/1985

FSC:8010

NIIN:00-142-9279

Kit Part:Y

MSDS Number: BDBTH

=== Responsible Party ===

Company Name:DESOTO, INC.

Address:1700 S MT PROSPECT RD

City:DES PLAINES

State:IL

ZIP:60017

Country:US

CAGE:32758

=== Contractor Identifica

tion ===

Company Name:DE SOTO INC

Address:1700 S MT PROSPECT RD

Box:City:DES PLAINES

State:IL

ZIP:60017

Country:US

Phone:708-391-9000

CAGE:96595

Company Name:DESOTO, INC.

Box:5030

CAGE:32758

=====
Composition/Information on Ingredients
=====

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction by Wt: 15.0%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RT

ECS #:EL6475000
Fraction by Wt: 10.0%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 5.00%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 10.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:STRONTIUM CHROMATE (SARA III)
CAS:7789-06-2
RTECS #:GB3240000
Fraction by Wt: 20.0%
OSHA PEL:0.1 PPM CRO3;CEILING
ACGIH TLV:0.0005MG CR/M3;A2;93
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC,IRRITATION, CNS
DEPRESSION,HEADACHE, DIZZINESS,UNCONSCIOUS. SKIN&EYE: IRRITATION.

===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPOSURE. RES

TIRE BREATHING. KEEP WARM &
QUIET. GET MEDICAL ATTN. SKIN: WASH W/WATER. REMOVE CONTAMINATED
CLOTHING. EYE:FLUSH IMMED. WITH WATER FOR AT LEAST 15 MIN.

===== Fire Fighting Measures =====

Flash Point:40F CC (4.4C)

Lower Limits:1.2

Extinguishing Media:CO*2, DRY CHEM, FOAM - NFPA CLASS B EXTINGUISHERS

Fire Fighting Procedures:H*2O SPRAY INEFF.IF H*2O USED,FOG NOZ

PREF.COOL CNTNRS W/WTR

Unusual Fire/Explosion Hazard:KEEP CNTNRS CLOSED. ISOLATE FRM HEAT
&

FLAME. CLSD CNTNRS MAY EXPLD IF EXPSD TO EXTRM HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 120F IN BLDGS DESIGNED FOR
STORAGE OF FLAMMABLE LIQUIDS. KEEP LEL BELOW 25% OF LIMIT. AVOID
F

REEFALL OF LIQUID GREATER THAN A FEW INCHES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. DO NOT
APP,LY TO HOT SURFACES. DO NOT SAND, FLAMECUT,BRAZE OR WELD WITHOUT
NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTR VENT-CHEM MECH FLTR.CNFND-AIR LN TYPE
RESP/HOOD

Ventilation:GEN DLTN OR LCL EXH TO KEEP BLW TLV OF MOST HAZ INGRDNT

Protective Gloves:REQUIRED

Eye Protec

tion:SFTY EYEWEAR FOR SPLASH

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT
W/CONTAMINATED CLOTHING

Supplemental Safety and Health

PRODUCT ALSO CONTAINS