

BATTENFIELD AMERICA,INC. -- WAY OIL -- 9150-00-145-0112

===== Product Identification =====

Product ID:WAY OIL

MSDS Date:01/01/1987

FSC:9150

NIIN:00-145-0112

MSDS Number: BDCCW

=== Responsible Party ===

Company Name:BATTENFIELD AMERICA,INC.

Address:1575 CLINTON ST

City:BUFFALO

State:NY

ZIP:14200

Info Phone Num:716-822-8410

Emergency Phone Num:716-822-8410

Preparer's Name:THOMAS G. MUSILLI

CAGE:KO10

5

=== Contractor Identification ===

Company Name:BATTENFELD AMERICA INC

Address:1575 CLINTON ST

Box:City:BUFFALO

State:NY

ZIP:14206

Country:US

Phone:716-822-8410

CAGE:61808

Company Name:BATTENFIELD AMERICA,INC.

Address:1575 CLINTON ST

City:BUFFALO

State:NY

ZIP:14206

Country:US

Phone:716-822-8410

CAGE:KO105

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients

=====

Ingred Name:MINERAL OIL
CAS:64742-65-0
RTECS #:PY8038500
Fraction by Wt: 50%
Other REC Limits:5 MG/M3

Ingred Name:MINERAL OIL
CAS:72623-83-7
Fraction by Wt: 44%

Ingred Name:POLYISOBUTYLENE
CAS:9003-27-4
RTECS #:UD1010000
Fraction by Wt: 2.0%

Ingred Name:SULFURIZED ISOBUTYLENE
CAS:68511-50-2
Fraction by Wt: 1.0%

Ingred Name:LEAD METHYL ESTER
CAS:68082-78-0
Fraction by Wt: 3.0%

===== Hazards Identification =====

Routes of Entry: Inhalation:NO
Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT AND DOES NOT SENSITIZE. VAPOR PRESSURE IS LOW ENOUGH TO BE NON-HAZARDOUS BY INHALATION. TOXICITY IS LOW BY INGESTION.
Explanation of Carcinogenicity:MFR CLAIMS NO CARCINOGENITY
Effects of Overexposure:EYE/SKIN:IRRITATION. INHALED:NONE REPORTED. INGESTION:NONE REPORTED.
Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDRER BEFORE REUSE. INHALED:NONE REPORTED. INGESTED:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:360F/182C
Autoignition Temp:Autoignition Temp Text:400F
Extinguishing Media:WATER FOG,CARBON DIOXIDE,DRY CHEMICAL,FOAM,EARTH/SAND
Fire Fighting Procedur

es:WATER MAY CAUSE FROTHING.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH INERT MATERIAL.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN LOW FIRE RISK AREA AWAY FROM
OXIDIZERS AND IGNITION SOURCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE EXPECTED TO BE
NEEDED.
Ventilation:NO SPECIAL VENTILATION NECESSARY
Protective Gloves:NEOPRENE,POLYETHYLENE
Eye Protection:FACE SHIELD IF SPLASH HAZARD IS HIGH
Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:700F/371C
Spec Gravity:0.89
Solubility in Water:NIL
Appearance and Odor:FATTY,FLUID,OIL

===== Stability and Reactivity Data =====

Stab
ility Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Stability Condition to Avoid:NONE REPORTED
Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.
MFR SUGGESTS INCINERATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United

States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.