

TESTING SYSTEMS,INC. -- SD-80B (PER MFR,THIS IS CLEANER) -- 6850-00-145-0255

===== Product Identification =====

Product ID:SD-80B (PER MFR,THIS IS CLEANER)

MSDS Date:01/01/1985

FSC:6850

NIIN:00-145-0255

Kit Part:Y

MSDS Number: BDCFL

=== Responsible Party ===

Company Name:TESTING SYSTEMS,INC.

Country:US

Emergency Phone Num:201-767-7300

CAGE:28257

=== Contractor Identification ===

Company Name:TESTING SYSTEMS,INC.

CAGE:28257

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 95.0%

OSHA PEL:100 PPM

Ingred Name:CARBON DIOXIDE

CAS:124-38-9

RTECS #:FF6400000

Fraction by Wt: 5.0%

OSHA PEL:5000 PPM

ACGIH TLV:5000PPM/30000STEL;93

===== Hazards Identification =====

Effects of Overexposure:INH:HIGH CONC RESULTS MILD DEPRESSION TO
CONVULSIONS & LOSS OF CONSCIOUSNESS.

===== First Aid Measures =====

asures =====

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T
INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF
NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE
ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point:FLAMMABL AEROSOL

Lower Limits:0.9%

Upper Limits:6.0%

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER SPRAY OR FOG

Fire Fighting P

rocedures:USE AIR SUPPLD RESCUE EQUIP IN ENCLOSD

AREA;COOL CONT W/H*2O

Unusual Fire/Explosion Hazard:SOME OF MATL MAY BURN. CONT MAY EXPLODE
IN HEAT OF FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION
SOURCES. STOP LEAK. H*2O SPRAY COOL CONT/DIVERT SPILL FROM
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL
ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL
ABSORB
ENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED.KEEP AWAY FROM
HEAT,SPARKS & OPEN FLAME.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W/SKIN.REMOVE
CONTAMINATED CLOTHING.WASH SKIN W/SOAP & WATER AFTER CONTACT.USE
W/ADEQUATE VENTILATION;IF SPILLED IN ENCLOSED AREA,OPEN
WINDOWS/DOORS.

===== Exposure Controls/Personal Protection =====

Respiratory Pr

rotection:HYDROCARBON VAP CANISTER OR SUPPLD-AIR HOSE MASK
IF NEEDED.

Ventilation:LOCAL EXHAUST:FACE VELCTY >6OFT/M;MECH:EXPLSV PROOF
EQUIPMNT

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:HYDROCARBON-INSOLUBLE APRON IF NEEDED.

Supplemental Safety and Health

KEY1:F1. THIS PRODUCT IS A KIT CONSISTING OF THREE PARTS.

CLEANER/REMOVER HAS PNI A. SINCE THIS COMPANY WAS SOLD TO AMERICAN
GAS; FOR PENETRANT AND DEVELOPER, SEE CAGE 03530, SAME N
SN.

===== Physical/Chemical Properties =====

HCC:V3

NRC/State Lic Num:NOT RELEVANT

Boiling Pt:B.P. Text:313-347F

Vapor Pres: