Product ID:MIL-C-81964.CLNG. CMPD, AVIONIC CMPDS MSDS Date:01/01/1985 FSC:6850 NIIN:00-148-7161 MSDS Number: BDCMB === Responsible Party === Company Name:ASPENGOLD CORPORATION Emergency Phone Num:505-345-1333 CAGE:9N369 === Contractor Identification === Company Name:ASPENGOLD CORPORATION CAGE:9N369

III) CAS:76-13-1 RTECS #:KJ4000000 Fraction by Wt: 74.7% OSHA PEL:1000PPM/1250STEL ACGIH TLV:1000PPM/1250STEL9192 Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III) CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 25% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Ingred Name:SILICONE FLUID RTECS #:VW1620000 Frac

tion by Wt: 0.3%
======================================
Effects of Overexposure:NARCOTIC
======================================
First Aid:MOVE TO FRESH AIR.IF BREATHING NOT INDICATED, APPLY ARTIFICIAL RESPIRATION. ADMINISTER OXYGEN.GET MEDICAL ATTENTION.
======================================
Flash Point:N.A. Extinguishing Media:NONE Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:SMALL SPILLS-MOP,WIPE,OR SOAK UP WITH ABSORBENT MATERIAL.LARGE SPILLS-EVACUATE AREA,FLUSH SPILL TO GROUND & LET EVAPORATE.
======================================
Handling and Storage Precautions:HANDLE WITH REASONABLE CARE.AVOID BREATHING VAPORS IN CONCENTATION OVER THE TLV 1000 PPM. Other Precautions:KEEP OFF SKIN & OUT OF EYES.WILL HAVE A DEFATTING ACTION
======================================
Respiratory Protection:NO SPECIAL EQUIPMENT NEEDED Ventilation:AS REQUIRED TO CONTROL TLV IN AIR Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES Supplemental Safety and Health THE 1,1,2 TRICHLORO-1,2,2-TRIFLUOROETHANE IS MIXED WITH POLY SILICON. THIS PRODUCT IS INERT AND VIRTUALLY NONTOXIC
======================================

HCC:V2 Boiling Pt:B.P. Text:117.7P Vapor Pres:6 Vapor D ensity:7.3 Spec Gravity:1.413 Solubility in Water:0.03 Appearance and Odor:VOLATILE,WATER WHITE,CLEAR,CHLORINATED SOLVENT Percent Volatiles by Volume:99.5

Stability Indicator/Materials to Avoid:YES HOT METALS,ELECTRIC ARCS,OPEN FLAMES. Stability Condition to Avoid:HOT METALS,OPEN FLAMES,WELDING ARCS Hazardous Decomposition Products:HYDROGEN CHLORIDE,PHOSGENE,HYDROGEN FLUORIDE

====== Disposal Considerations

Waste Disposal Methods:BURY AWAY FROM WATER SUPPLY OR ALLOW SOLVENT TO EVAPORATE ATMOSPHERE,AT A SAFE DISTANCE FROM INHABITED BUILDINGS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizi ng this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.