

PERMAGILE-SALMON LTD -- PG-2125,PART B -- 8030-00-159-5032

===== Product Identification =====

Product ID:PG-2125,PART B

MSDS Date:01/01/1985

FSC:8030

NIIN:00-159-5032

MSDS Number: BDDCY

=== Responsible Party ===

Company Name:PERMAGILE-SALMON LTD

Emergency Phone Num:516-349-1100

CAGE:HO069

=== Contractor Identification ===

Company Name:PERMAGILE INDUSTRIES INC

Address:101 COMMERCIAL STREET

City:PLA

INVIEW

State:NY

ZIP:11803

Country:US

Phone:516-349-1100/800-424-9300(CHEMTREC)

CAGE:13549

Company Name:PERMAGILE-SALMON LTD

CAGE:HO069

===== Composition/Information on Ingredients =====

Ingred Name:DIETHYLENE TRIAMINE

CAS:111-40-0

RTECS #:IE1225000

Fraction by Wt: 2%

OSHA PEL:1 PPM

ACGIH TLV:S, 1 PPM; 9192

Ingred Name:GLYCERIN

CAS:56-81-5

RTECS #:MA8050000

Fraction by Wt: 3%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 (MIST) 9293

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000
Fraction by Wt: 4.5%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 5%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:2,4,6 TRI (DIMETHYLAMINO METHYL) PHENOL
CAS:90-72-2
RTECS #:SN3500000
Fraction by Wt: 14%

===== Hazards Identification =====

Effects of Overexposure:EYE/SIN: IRRITATION. VA
PORS: HEADACHE,DIZZINESS

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MINUTES,GET MEDICAL ATTN. SKIN:
REMOVE CONTAMINATED CLOTHING & WASH AFFECTED AREA WITH SOAP &
WATER. INHALATION: REMOVE FROM EXPOSURE.

===== Fire Fighting Measures =====

Flash Point:>200F/93C (COC)
Extinguishing Media:CO*2,DRY CHEMICAL,WATER FOG,FOAM

===== Accidental Release Measures =====

Spil
I Release Procedures:ABSORB SPILLAGE WITH RAGS,SAWDUST OR SAND.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT AND OPEN FLAME.
USE ONLY WIT ADEQUATE VENTILATION.
Other Precautions:AVOID BREATHING VAPORS AND EYE/SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.
Ventilation:LOCAL/MECHANICAL
P

rotective Gloves:RUBBER/PLASTIC

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:COVERALLS OR APRON.

Supplemental Safety and Health

ADD INGREDIENTS: FUMED SILICA,3%;MAGNESIUM SILICATE,28%POLYAMIDE
RESIN,38%;IRON OXIDE BLACK,1.5%. PART B OF A TWO PART KIT.

CONTAINER SIZE: 15 LB. TYPE 2.KEY1:N1.

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.18

Evaporation Rate & Reference: