

SCM, GLIDDEN DURKEE DIVISION -- TT-T-266 THINNER, 907 S 2100 -- 8010-00-160-5788

===== Product Identification =====

Product ID: TT-T-266 THINNER, 907 S 2100

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00-160-5788

MSDS Number: BDDGJ

=== Responsible Party ===

Company Name: SCM, GLIDDEN DURKEE DIVISION

Address: 925 EUCLID AVE

City: CLEVELAND

State: OH

ZIP: 44115

Country: US

CAGE: KO354

=== Contractor Identification ===

Company Name: GLIDDEN CO MEMBER OF ICI WORLD PAINTS

Address: 925 EU

CLID AVE

Box: 15049

City: CLEVELAND

State: OH

ZIP: 44115

Country: US

Phone: 216-344-8000

CAGE: 72818

Company Name: SCM, GLIDDEN DURKEE DIVISION

Address: 925 EUCLID AVE

Box: City: CLEVELAND

State: OH

ZIP: 44115

Country: US

CAGE: KO354

===== Composition/Information on Ingredients =====

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS #: NT8050000

Fraction by Wt: 6%

OSHA PEL: 400 PPM/500 STEL

ACGIH TLV: 400 PPM/500 STEL; 9192

Ingred Name: ISOBUTYL ALCOHOL (SARA III)

CAS: 78-83-1

RTECS #: N

P9625000
Fraction by Wt: 9%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 50%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 35%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
==== Hazards Identification =====

Effects of Overexposure:EYE/SKIN/RESPIRATORY TRACT: IRRIT. POSS DERMAT
ON REPEATED/PROLONGED CONTACT

===== First Aid Measures =====

First Aid:INHAL:REMOVE FROM EXPOSURE TO WELL VENTED AREA. RESTORE
BREATHING. GET MEDICAL AID. SKIN: WIPE W/ CLEAN CLOTH,WASH W/ SOAP
& WATER. EYE: FLUSH W/ WATER FOR 15 MINUTES. GET MEDICAL AID.

===== Fire Fighting Measures =====
=

Flash Point:40F;4.44C; TCC
Lower Limits:1.2
Extinguishing Media:CO*2,DRY CHEM,FOAM,WATER SPRAY MAY BE INEFFECTIVE
Fire Fighting Procedures:USE WATER SPRAY TO COOL HEAT EXPOSED CANS
Unusual Fire/Explosion Hazard:CLOSED CANS MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT OR FIRE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. VENT AREA. MOP SPILL
W/ INERT ABSORBENT. BURN SWEEPINGS IN SAFE AREA.

===== Han

ding and Storage =====

Handling and Storage Precautions:STORE BELOW 100F. KEEP CONTAINERS
CLOSED & AWAY FORM HEAT & OPEN FLAME.

Other Precautions:AVOID PROLONG CONTACT WITH SKIN & BREATHING OF VAPORS
OR SPRAY MIST. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESPIRATOR FOR PARTICULAR
EXPOSURE OF CONCERN(MFR)

Ventilation:GENERAL/LOCAL-TO KEEP BELOW TLV

Protective Gloves:SOLVE

NT RESIST

Eye Protection:SPLASH PROOF GOGGLES

Supplemental Safety and Health

CONTAINER: 5 GALLON PAIL

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:179-243F

Vapor Pres:37

Vapor Density:>1

Spec Gravity:0.834

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTAMINATION WITH FOREIGN MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:MFR STATES DO NOT INCINERATE CLOSED CONTAINERS.
DISPOSE IAW FED, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use.

Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.