

GEORGE SENN COMPANY,DIV. OF GLOBE SOLVENTS -- TT-T-266D,THINNER,DOPE AND LACQUER
-- 8010-00-160-5788

===== Product Identification =====

Product ID:TT-T-266D,THINNER,DOPE AND LACQUER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5788

MSDS Number: BDDGM

=== Responsible Party ===

Company Name:GEORGE SENN COMPANY,DIV. OF GLOBE SOLVENTS

Address:2200 E WESTMORELAND ST

City:PHILADELPHIA

State:PA

ZIP:19134-32

29

Country:US

CAGE:KO352

=== Contractor Identification ===

Company Name:GEORGE SENN COMPANY,DIV. OF GLOBE SOLVENTS

Address:2200 E WESTMORELAND ST

Box:City:PHILADELPHIA

State:PA

ZIP:19134-3229

Country:US

CAGE:KO352

Company Name:SENN GEORGE INC

Address:2200 E WESTMORELAND ST

Box:City:PHILADELPHIA

State:PA

ZIP:19134-3229

Country:US

CAGE:86944

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt:

15%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:LACTOL SPIRITS (50% DISTILLATION TEMPERATURE 206F)
Fraction by Wt: 30%
ACGIH TLV:300 PPM (MFR)

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 18%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 15%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:
400 PPM/500STEL;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 22%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:HEADACHE,NAUSEA,DROWSINESS.

=====
===== First Aid Measures =====

First Aid:FLUSH SKIN W/WATER.IMMEDIATELY FLUSH EYES W/WATER AT LEAST 15

MIN.CALL MD. INHALATION:REMOVE TO FRESH AIR,GIVE ARTIFICIAL RESPIRATION,IF NECESSARY.CALL MD.

=====
Fire Fighting Measures
=====

Flash Point:15F TCC
Extinguishing Media:WATER SPRAY,CO*2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,RECOVER FREE LIQUID.

=====
Handling and Storage =
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS & OPEN FLAME.AVOID PROLONGED BREATHING OR CONTACT W/SKIN.

=====
Exposure Controls/Personal Protection
=====

Ventilation:LOCAL EXHAUST-YES. MECHANICAL-YES
Protective Gloves:NEOPRENE
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:NEOPRENE APRON
Supplemental Safety and Health
ITEM COMPOSITION IS IN PERCENT BY VOLUME.SPECIFIC GRAVITY GIVEN @ 60/60F. MFR STATES PETROLEUM DISTILLATES (LACTOL SPIRITS,TOLUOL) DO NOT CONTAIN BENZENE OR CYCLOHEXANE.

=====
Physical/Chemical Properties
=====

HCC:F3
Boiling Pt:B.P. Text:180F (IBP)
Spec Gravity:0.800
Solubility in Water:APPRECIABLE
Appearance and Odor:WATER WHITE & MILD
Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS,CONCENTRATED SULFURIC ACID
Hazardous Decomposition Products:CARBON

MONOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR EVAPORATE IN ACCORDANCE
W/LOCAL,STATE & FEDERAL REGULATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. An
y person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.