View NSN Online: https://aerobasegroup.es/nsn/8010-00-160-5798

4-TEX INDUSTRIES -- ORGANIC PAINT REMOVER -- 8010-00-160-5798

Product ID:ORGANIC PAINT REMOVER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5798

MSDS Number: BDDHK === Responsible Party ===

Company Name:4-TEX INDUSTRIES Emergency Phone Num:206-392-9137

CAGE:KO358

=== Contractor Identification ===
Company Name:4-TEX INDUSTRIES

CAGE:KO358

Company Name: GENERAL SERVICES

ADMINISTRATION FEDERAL SUPPLY SVC

Address: CYSTAL MALL BLDG 4 1941 JEFFERSON DAVIS

Box:HWY

City:WASHINGTON

State:DC ZIP:20406 Country:US CAGE:80244

======= Composition/Information on Ingredients ========

Ingred Name:SOLVENTS Fraction by Wt: 100%

Ingred Name: ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000 Fraction by Wt: 33% OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0 RTECS #:NT8

Fraction by Wt: 33% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192
Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 33% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
======================================
Effects of Overexposure:REMOVE INDIVIDUAL TO FRESH AIR.IF BREATHING IS DIFFICULT,ADMINISTER OXYGEN.DO NOT GIVE STIMULANTS
======================================
First Aid:CALL A PHYSICIAN.
======================================
Flash Point:0 F TCC -18 C Lower Limits:1.27 Upper Limits:90.0 Extinguishing Media:WATER FOG, CO*2,DRY CHEMICAL Unusual Fire/Explosion Hazard:SELF-CNTND BRTHNG APPARATUS
========= Accidental Release Measures ==========
Spill Release Procedures:STOP SPILL AT ONCE,KEEP UNPROTECTED PEOPLE FROM AREA.MATERIAL MUST BE TAKEN UP W/ABSORBANT MATERIAL.
====
======================================
Handling and Storage Precautions:KEEP IN COOL PLACE.EXTREMELY FLAMMABLE Other Precautions:KEEP AWAY FROM CHILDREN.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NIOSH/MSHA APPRVD IF TLV IS EXCEEDED Ventilation:LOC EXHAUST-YES MECH-YES (NON-FLAMMABLE) Protective Gloves:CHEM RESIST GL Eye Protection:SAFETY GLASSES Supplemental Safety and Health
========= Physical/Chemical Prop

HCC:F2 Boiling Pt:B.P. Text:131F 56 C Vapor Pres:400 Vapor Density:HEAV Spec Gravity:.815 Evaporation Rate & Description Rate &
Percent Volatiles by Volume:99
========== Stability and Reactivity Data ==============
Stability Indicator/Materials to Avoid:YES
======== Disposal Considerations ============
Waste Disposal Methods:ACCORDING TO LOCAL CODES.
Disclaimer (provi ded with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

erties =========

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.