

STAHL SOAP CORP -- TT-R-251 -- 8010-00-160-5800

===== Product Identification =====

Product ID:TT-R-251

MSDS Date:01/01/1985

FSC:8010

NIIN:00-160-5800

MSDS Number: BDDHN

=== Responsible Party ===

Company Name:STAHL SOAP CORP

Address:1413 WILLOW AVE

City:HOBOKEN

State:NJ

ZIP:07030-3309

Country:US

CAGE:97845

=== Contractor Identification ===

Company Name:STA-LUBE INC

Address:3039 ANA ST

Box:City:RANCHO DOMINGUEZ (PART OF COMPTON)

State:CA

ZIP:90221

Country:US

Pho

ne:310-664-2121/800-424-9300(CHEMTREC)

CAGE:33876

Company Name:STAHL SOAP CORP

Address:1413 WILLOW AVE

Box:City:HOBOKEN

State:NJ

ZIP:07030-3309

Country:US

CAGE:97845

===== Composition/Information on Ingredients =====

Ingred Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 85%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

ACGIH TLV:50 PPM, A2; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ALCOHOL

(METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 15%
OSHA PEL:S,200PPM/250STEL
ACGIH TLV:S,200PPM/250STEL; 93
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:DIZZINESS,IRRIT.OF MUCOUS MEMBRANES,CARDIAC
DEPRESSION,NARCOSIS.

===== First Aid Measures =====

First Aid:REMOVE FR.SKIN W/WATER,REMOVE PATIENT TO FRESH AIR IF
OVERCOME W/VAPOR.IF INJE
STED,INDUCE VOMITING,& CONTACT
DR.IMMED.POISON! FOR EYE CONTACT,FLUSH W/WATER & CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:85F TOC 29C
Extinguishing Media:WATER,DRY CHEMICAL
Unusual Fire/Explosion Hazard:PRODUCT MAY BECOME FLAMMABLE IF ENOUGH
METHYLENE CHLORIDE IS ALLOWED TO EVAPOR.CONTCT W/OPEN (SUPPL)

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILLS:MOP UP,OR SOAK UP W/ABS
ORBENT
MATERIAL USING PROPER PROTECTIVE EQPMT.BURY. LG SPILLS:EVACUATE
AREA,USING PROPER PROTECTIVE EQPMT FLUSH SPILL.TO GROUND & LET
EVAPORATE.KEEP OUT OF WATER SU PPLY & AWAY FR INHABITED BUILDINGS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AT TEMPERATURES BELOW 100F.
Other Precautions:CONSUMER PRODUCT SAFETY COMM.HAS STATED NO PROPER
METHOD EXISTS FOR DETERMINING FLASH POINT OF THIS PRODUCT.

===== Expo

sure Controls/Personal Protection =====

Respiratory Protection:GAS MASK F/ORGANIC VAP IF ATMOSP CONTAINS
EXCESSIVE VAPORS

Ventilation:LOC EXHAUST-PROVIDE ADEQ VENTILATION

Protective Gloves:POLYETHYLENE

Eye Protection:UNBREAKABLE GLASS GOGGLES

Supplemental Safety and Health

UNUS.FIRE & EXPLOS HAZ:FLAME CAN PRODUCE TOXIC GAS.

HAZ.DECOMP:CHLORIDE,CHLORINE & PHOSGENE

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:104F 40C

Vapor Pr

es:316

Vapor Density:1.11

Spec Gravity:1.23

Evaporation Rate & Reference:WATER=1