View NSN Online: https://aerobasegroup.es/nsn/8010-00-161-7379

AMERON PROTECTIVE COATINGS -- BLACK 17 -- 8010-00-161-7379

============= Product Identification ==============

Product ID:BLACK 17 MSDS Date:01/01/1987

FSC:8010

NIIN:00-161-7379

MSDS Number: BDDMY === Responsible Party ===

Company Name: AMERON PROTECTIVE COATINGS

Address: 201 NORTH BERRY STREET

City:BREA State:CA

ZIP:92622-1020 Country:US

Info Phone Num:714-529-1951

Emergency Phone Num:714-529-1951

CAGE:0Y2E4

=== Co

ntractor Identification ===

Company Name: AMERON PROTECTIVE COATINGS

Address: 201 NORTH BERRY STREET

Box:1020 City:BREA State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTYL ACETATE

CAS:110-19-0

RTECS #:AI4025000 Fraction by Wt: 8%

Other REC Limits:150 PPM

OSHA PEL:150 PPM

ACGIH TLV:713 MG/CUM EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:BENZIN, NAPHTHA, MINERAL SPIRITS, PETROLEUM NAPHT

HA

CAS:8030-30-6

RTECS #:DE3030000 Fraction by Wt: 15%

Other REC Limits: STEL 400 PPM

OSHA PEL:100 PPM ACGIH TLV:300 PPM

Ingred Name: ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL

CAS:78-83-1

RTECS #:NP9625000 Fraction by Wt: 8%

Other REC Limits:50 PPM OSHA PEL:300 MG/CUM ACGIH TLV:152 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (IARC CARC- GROUP 3) *97-3*

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 7%

Other REC Limits:375 MG/CUM

OSHA PEL:100 PPM ACGIH TLV:100

PPM

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL ACETATE (N-BUTYL ACETATE) *97-3*

CAS:123-86-4

RTECS #:AF7350000 Fraction by Wt: 19%

Other REC Limits:150 PPM OSHA PEL:710 MG/CUM ACGIH TLV:713 MG/CUM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

============= Hazards Identification ========================

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: INHALATION: ANESTHETIC. IRRI

RESPIRATORY TRACT & MAY CAUSE NERVOUS SYSTEM DEPRESSION. SKIN/EYE: IRRITATION.
Explanation of Carcinogenicity:NONE Effects of Overexposure:IRRITATION
Lifects of Overexposure.iiXXTATION
======================================
First Aid:SKIN/EYES: FLUSH W/WATER. INHALATION: REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.
======================================
Flash Point Method:TCC Flash Point:30F Lower Limits:1.1 Extinguishing Media:S MALL FIRES: CO2/DRY CHEMICAL. LARGE FIRES: FOAM Fire Fighting Procedures:USE SELF CONTAINED BREATHING APPARATUS. Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT EXPLODE.
=========== Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION; HOT SURFACES, ELECTRICAL STATIC/FRICTIONAL SPARKS. AVOID BREATHING VAPORS. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE/COMBUSTIBLE. Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR. RESPIRATOR USED BASED ON CHEMICAL CONDITION & CONDITIONS OF USE. Ve

TATION OF

======= Disposal Considerations =============

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expr

essly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.