

EASTMAN KODAK CO. -- 199 7915,VERSAMAT 885 DEVELOPER STATER -- 6750-00-165-7189

===== Product Identification =====

Product ID:199 7915,VERSAMAT 885 DEVELOPER STATER

MSDS Date:05/23/1985

FSC:6750

NIIN:00-165-7189

MSDS Number: BDDXN

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 1-5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:SODIUM BROMIDE

CAS:7647-15-6

RTECS #:VZ3150000

Fraction by Wt

: 30-40%
Other REC Limits:NONE ESTABLISHED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 60-70%
Other REC Limits:NONE ESTABLISHED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Effects of Overexposure:EYES,SKIN,MUCOUS MEMBRANES:LOW HAZARD,PER MFG.
PRUDENCE REGARDING CHEMICAL IS SUGGESTED.

===== First Aid Measures =====

First Aid:EYES,SKIN,MUCOUS MEMBRANES:FLUSH W LG AMTS H*2O AT LEAST 15
MIN; INHALE:REMOVE TO FRESH AIR,KEP CALM;INGEST:RISE MOUTH,DRINK
EXCESS WATER,DO NOT INDUCE VOMIT.GET IMMEDIATE MEDICAL ATTENTION
FOR EYES,I NGEST,INHALE, OR SKIN BURNS(MFG:NONE INDICATED)

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE.
Fire
Fighting Procedures:WEAR SELF-CNTND BRTHG APP;WATER SPRAY COOL
CONTAINERS.
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF
FIRE.ACID SOLUTION;AVOID PHYSICAL CONTACT.

===== Accidental Release Measures =====

Spill Release Procedures:DO NOT TOUCH SPILLED MATERIAL. WEAR PROTECTIVE
EQUIPMENT.STOP LEAK IF POSSIBLE WITHOUT RISK. SM SP:ABSORB W
COMMERCIAL ABSORBENT & PUT IN APPR CONTAINERS. LG SP: CONTAIN W
DIKE & TRANSFER TO APPR CONT AI

NERS (SOLUTION IS ACID).

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AIRE; PROTECT FROM PHYSICAL DAMAGE & AVOID CONTACT WITH SKIN(ACID
SOLUTION).AVOID CONTACT WITH ALKALIES.

Other Precautions:REMOVE & WASH CONTAMINATED CLOTHING. MAINTAIN STRICT
HYGIENE.MFG INDICATED PRODUCT OF LOW HAZARD, CONTRADICTING PH
INFO,AND THAT NO PROTECTIVE EQUIPMENT OR SPECIAL PRECAUTIONS
NEEDED.

=====

=== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR VAPOR EXPOSURE, USE APPR ORGANIC VAPOR
RESPIRATOR.

Ventilation:ADEQUATE TO ELIMINATE FUMES:MECHANICAL(GEN/LOCAL EXHAUST)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL WORK CLOTHING;FACE SHIELD WHEN USING
PRODUCT.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:C3

Boiling Pt:B.P. Text:>212F,>100C

V

apor Pres:32

Vapor Density:0.6

Spec Gravity:1.35

pH: