

AMERON PROTECTIVE COATINGS -- 797 801 CLEAR TT L 26B AM 2 -- 8010-00-166-1688

=====
Product Identification
=====

Product ID:797 801 CLEAR TT L 26B AM 2

MSDS Date:01/01/1987

FSC:8010

NIIN:00-166-1688

MSDS Number: BDFBB

=== Responsible Party ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

City:BREA

State:CA

ZIP:92622-1020

Country:US

Info Phone Num:714-529-1951

Emergency Ph

one Num:714-529-1951

CAGE:0Y2E4

=== Contractor Identification ===

Company Name:AMERON PROTECTIVE COATINGS

Address:201 NORTH BERRY STREET

Box:1020

City:BREA

State:CA

ZIP:92622-1020

Country:US

Phone:714-529-1951

CAGE:0Y2E4

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL
CARBINOL (IARC-GROUP 3) *98-2*

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 4.4%

Other REC Limits:400 PPM

OSHA PEL:400 PPM

ACGIH TLV:400

PPM

Ingred Name:ISOBUTANOL, 2-METHYL-1-PROPANOL, ISOBUTYL ALCOHOL
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 9.5%
Other REC Limits:50 PPM
OSHA PEL:300 MG/CUM
ACGIH TLV:152 MG/CUM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL BENZENE *98-2*
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: 0.8%
Other REC Limits:100 PPM
OSHA PEL:435 MG/CUM
ACGIH TLV:434 MG/CUM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE,TOLUOL (IARC CARC- GROUP 3) *98-2*
CAS:108-88-3
RTECS
#:XS5250000
Fraction by Wt: 32.2%
Other REC Limits:375 MG/CUM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VM&P NAPHTHA
Fraction by Wt: 4.3%

Ingred Name:ISOBUTYL ACETATE
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 27.8%
Other REC Limits:150 PPM
OSHA PEL:150 PPM
ACGIH TLV:713 MG/CUM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CELLOSOLVE ACETATE
Fraction by Wt: 5%

===== Hazards Identification =====

Rout

es of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: ANESTHETIC. MAY CAUSE
IRRITATION OF THE RESPIRATORY TRACT. NERVOUS SYSTEM DEPRESSION.
SKIN/EYES: PRIMARY IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, DIZZINESS, STAGGERING
GAIT, CONFUSION, UNCONSCIOUSNESS, COMA

===== First Aid Measures =====

First Ai
d:SKIN/EYES: FLUSH W/PLENTY OF WATER. INHALATION: REMOVE TO
FRESH AIR. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:28F
Lower Limits:0.9
Extinguishing Media:SMALL: CO2/DRY CHEMICAL. LARGE: POLYMER FOAM
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP.

===== Ac
cidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT &
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED & PROTECTED FOR STORAGE OF
FLAMMABLE LIQUIDS.
Other Precautions:DON'T TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED
WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.
DON'T FLAME CUT/WELD COATED MATERIAL W/O RESPIRATOR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:OUTDOOR/OPEN AREA: APPROVED MECHANICAL FILTER
RESPIRATOR TO REMOVE AIR BORNE PARTICLES OF OVERSPRAY. RESTRICTED
AREA: APPROVED CHEMICAL-MECHANICAL FILTERS DESIGNED TO REMOVE
GAS/VAPORS. CONFINED AREA: APPROVED AIR TYPE RESPIRATORS/HOODS.
Ventilation:GENERAL DILUTION/LOCA

L EXHAUST: TO KEEP HAZARDOUS
INGREDIENTS BELOW ACCEPTABLE LIMITS.

Protective Gloves:REQUIRED

Eye Protection:SAFETY EYEWEAR W/SPLASHPROOF PROTECTION

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE
REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:175-329F

Vapor Density:>1

Evaporation Rate & Reference
:SLOWER THAN ETHER

Percent Volatiles by Volume:85

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES, HEAT, HOT SURFACES,
ELECTRICAL/STATIC/FRICTIONAL SPARKS & OTHER IGNITION SOURCES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL, STATE & FEDERAL
REGULATIONS. INCINERATE IN APPROVED FACILITY. DON'T INCINERATE
CLOSE
D CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.