

AMERON INDUSTRIAL COATINGS DIVISION -- BLUE 35044;787-503;LACQUER,CAMOUFLAGE --
8010-00-166-3145

===== Product Identification =====

Product ID:BLUE 35044;787-503;LACQUER,CAMOUFLAGE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-166-3145

MSDS Number: BDFBR

==== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone

Num:714-529-4597

Emergency Phone Num:714-529-4597

CAGE:09869

==== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 16.3%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingre

d Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 8.6%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 3.5%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 7.1%
OSHA PEL:400 PPM/500 STEL
ACGIH TL
V:400 PPM/500STEL;9192

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 19.3%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE
CNS DEPRSSN W/HDACHE, DIZ, UNCON,COMA. SKIN & EYE:IRRIT

===== First Aid Measures =====

First Aid:.. IN CASE OF CONTA

CT, FLUSH SKIN & EYES W/PLENTY OF WATER
WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH
AIR. CALL A PHYSICIAN IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:40F TCC
Extinguishing Media:SM FIRES:CO²,DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP

====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT
SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING
VAPORS. ENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY
IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ DO NOT TAKE
INTERA
LLY. ADD LABEL WARNING.

Other Precautions:GROUND CONTANERS WHEN POURING. AVOID FREE FALL OF
LIQ. IN EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED
MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.
DOT:FLAM LIQUID.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSED:AIR-LINE TYPE
Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV
FUME

Protective Gloves:YES

Eye Protecti

on:YES, FOR SPLSH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING
Supplemental Safety and Health

MFG GIVES LEL OV 1.3, HOWEVER, THE LOWEST LEL IS 1.0, FOR XYLENE. VAPOR
PRESSURE:31.2; VAPOR DENSITY:HEAVIER THAN AIR. WT PER GALLON:9.0 LBS

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175-287F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:73.0

===== Stability and Reactivity Data ===

=====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRES, HEAT & HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods: DO NOT INCINERATE CLOSED CONTAINERS DISPOSE IN ACCORDANCE W/FED., STATE & LOCA REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in n

o manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.