

PRATT AND LAMBERT INC -- 787-101 -- 8010-00-166-3151

===== Product Identification =====

Product ID:787-101
MSDS Date:01/01/1985
FSC:8010
NIIN:00-166-3151
MSDS Number: BDFCB
=== Responsible Party ===
Company Name:PRATT AND LAMBERT INC
Address:945 BURLINGTON
Box:206
City:KANSAS CITY
State:MO
ZIP:64141
Country:US
Emergency Phone Num:316-733-1361
CAGE:92216
=== Contractor Identification ===
Company Name:PRATT AND LAMBERT INC
Address:945 BURLINGTON
Box:206
City:KANSAS CITY
State:MO
ZIP:64141
Country:US
CAGE:92216

===== Composition/Information on Ingredients =====

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 15.0%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 15.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA

Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)
CAS:78-83-1
RTECS #:NP9625000
Fraction by Wt: 8.0%
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: < 5%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fract
ion by Wt: 8.0%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTHETIC & IRRIT. TO
AIRWAY;SKIN/EYE:IRRIT. ;HEADACHE,DIZZY,COMA

===== First Aid Measures =====

First Aid:SKIN/EYE:FLUSH WITH PLENTY OF WATER WHILE REMOVING
CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR. CALL MD. IF
SYMPTOM

S PERSIST.

===== Fire Fighting Measures =====

Flash Point:44F, 7 C, TCC

Lower Limits:1.0

Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE
FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE
FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL
SOURCES OF IGNITION (FLAMES,HOT
SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE
AMTS.IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS
ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD
BE GROUNDED

WHEN POURING,AVOID FREE FALL IN EXCESD OF A FEW INCHES, DO NOT
FLAME CUT,BRAZE, OR WELD COATED MATERIAL WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY &
WELDING.

Protective Gloves:ALOT OF CONTACT

Eye Protection:YES,IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CON

TACT TO

CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 79-142 C, ALSO CONTAINS MOLYBDATE ORANGE < 5%, METHYL
ETHYL KETONE