

DEFT CHEMICAL COATINGS -- LXP-3015 CATALYST,BROWN 20400,ISOCYANATE --
8010-00-181-7049

=====
===== Product Identification =====

Product ID:LXP-3015 CATALYST,BROWN 20400,ISOCYANATE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-181-7049

MSDS Number: BDGGY

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

Emergency Phone Num:71

4-549-8911

CAGE:EO418

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====
===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 25.0%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 L

=====
===== Hazards Identification =====

Effects of Overexposure: EYE IRRITANT. SOLVENTS MAY IRRITATE SKIN. MAY IRRITATE OR CAUSE NARCOSIS IF INHALED.

=====
===== First Aid Measures =====

First Aid: SKIN: WIPE OFF WITH RAG, FLUSH WITH WATER. WASH WITH SOAP & WATER. EYES: FLUSH WITH WATER 10 MIN, SEE EYE DOCTOR. INHALED: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. INGESTED: RINSE MOUTH. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point: 28F/-2.2C TOC
Lower Limits: UNK
Upper Limits: UNK
Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL.
Fire Fighting Procedures: WEAR SCBR, WATER SPRAY TO COOL EXPOSED CONT; DO NOT USE H₂O JET
Unusual Fire/Explosion Hazard: CONTAINERS MAY EXPLODE IN HEAT OF FIRE. DO NOT APPLY TO HOT SURFACES. AVOID SPARKS, OPEN FLAMES.

=====
===== Accidental Release Measures =====

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. PROVIDE VENTILATION. STOP LEAK. H₂O SPRAY TO COOL CONTR, IF HOT. ABSORB W. COMMERCIAL ABSORBENT, PLACE IN COVERED CONTR. MFR SUGGEST: ABSORB W RAGS, OTHER ABSORBENT. FLUSH W. LARGE VOLUME OF WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED, LOW FIRE RISK AREA. KEEP CONTAINERS TIGHTLY CLOSED. (MOISTURE SENSITIVE). PROTECT FROM PHYSICAL DAMAGE.

Other Preca

utions:MAINTAIN STRICT HYGIENE,AVOID PHYSICAL CONTACT,REMOVE
& WASH CONTAMINATED CLOTHING.AVOID PROLONGED INHALATION OF
VAPORS.USE FRESH AIR SUPPLY MASK IF VENTILATION IS POOR.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR EXPOSURE:SELF-CNTND BRTU APP/APPR
RESPIRATOR;GOOD VENTILATION.

Ventilation:USE ADEQUATE VENTILATION W. EXHAUST FAN.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:CARTRID

GE TYPE RESPIR WITH PARTICULATE
FILTERS.

Supplemental Safety and Health

TWO PART KIT; THIS DESCRIBES CATALYST; SEE P/N IND "B" FOR OTHER
INGRED OF THIS CATALYST. ALSO SEE P/N IND A FOR BASE OF THIS KIT.
SAME NSN: SPEC REF: NAI-1290; ALSO KNOWN AS "DEFTHANE CATALYS
T". KEY1:F3.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:160-329F

Vapor Pres:UNK

Vapor Density:>1

Spec Gravity:0.95

Evaporation Rate & Reference: