

ILLINOIS BRONZE POWDER AND PAINT COMPANY -- IB NO 2612 -- 8010-00-181-7791

=====
Product Identification
=====

Product ID:IB NO 2612

MSDS Date:01/01/1985

FSC:8010

NIIN:00-181-7791

MSDS Number: BDGMS

=== Responsible Party ===

Company Name:ILLINOIS BRONZE POWDER AND PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Info Phone Num:312-488-8001

Emergency Pho

ne Num:800-228-5635

CAGE:91794

=== Contractor Identification ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 22.2%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (S

ARA III)
CAS:75-09-2
RTECS #:PA8050000
Fraction by Wt: 33.3%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION-ANESTHETIC;IRRITATION OF RESPIRATORY TRACT;DIZZINESS.SKIN OR EYE-PRIMARY IRRITATION

=====
First Aid Measures
=====

First Aid:FUMES-REMOVE FROM EXPOSURE.MOVE TO FRESH AIR.EYES-FLUSH WITH LA
RGE AMOUNTS OF WATER FOR AT LEAST 15 MIN. CALL
PHYSICIAN.SKIN-WIPE OFF WITH TOWEL.REMOVE REMAINDER WITH MINERAL
SPIRITS OR LACQUER REMOVE R.WASH WITH SOAP & WATER

=====
Fire Fighting Measures
=====

Flash Point:-40F,-40C
Lower Limits:1.3%
Extinguishing Media:NFPA CLASS B EXTINGUISHERS
Fire Fighting Procedures:WATER TO COOL CONTAINERS WEAR GOGGLES AND
BREATHING APPARATU
Unusual Fire/Explosion Hazard:CANS WILL RUPTURE AT 190F AND DISCHARGE
FLAMMAB
LE CONTENTS

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING
VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA
CLASS 1A FLAMMABLE LIQUIDS
Other Precautions:DO NOT SPRAY IN EYES. DO NOT PUNC

TURE OR INCINERATE

CANS.DO NOT FLAME CUT,BRAZE OR WELD WITHOUT BUR. OF MINES APPROVED
RESPIRATOR OR APPROPRIATE VENTILATION

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE FOR CASUAL USE
Ventilation:DILUTION OR EXHAUST TO KEEP BELOW TLV
Protective Gloves:NONE
Eye Protection:NO SPECIAL REQUIRED
Supplemental Safety and Health
B.P.RANGE 6-199C

===== Physical/Chemical Properties =====

HCC:V3
Boiling Pt:B.P. Text:
42-391F
Percent Volatiles by Volume:89

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:HCL,CO,PHOSGENE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling a
gencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.