

IMPERIAL OIL CO.,INC. -- MIL-L-9000H 9250 IMP-9000GB -- 9150-00-181-8097

=====
Product Identification
=====

Product ID:MIL-L-9000H 9250 IMP-9000GB

MSDS Date:06/02/1992

FSC:9150

NIIN:00-181-8097

MSDS Number: BDGPR

=== Responsible Party ===

Company Name:IMPERIAL OIL CO.,INC.

Address:ORCHARD PLACE

Box:279

City:MORGANVILLE

State:NJ

ZIP:07751

Country:US

Info Phone Num:908-591-9400

Emergency Phone Num:9

08-591-9400

Preparer's Name:WILLIAM J. MAHONEY

CAGE:58563

=== Contractor Identification ===

Company Name:IMPERIAL OIL CO INC

Address:FOOT OF ORCHARD PL

Box:279

City:MORGANVILLE

State:NJ

ZIP:07751

Country:US

Phone:732-591-9400/FAX: 732-591-8825

CAGE:58563

=====
Composition/Information on Ingredients
=====

Ingred Name:REFINED HEAVY PARAFFINIC DISTILLATES/LUBE OIL BASE STOCK

CAS:64741-88-4

Fraction by Wt: >98%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV

:5 MG/M3 (OIL MIST)

Ingred Name:ZINC DIALKYL DITHIOPHOSPHATE & ZINC DIARYL DITHIOPHOSPHATE
(MIXED)

CAS:68649-42-3

Fraction by Wt: .03-.04%

Other REC Limits:NONE SPECIFIED

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: .6-.7%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:CHLORINE AS CHLORO-ORGANO COMPLEX

Fraction by Wt: .04-.05%

Other REC Limits:NONE SPECIFIED

Ingred Name:CALCIUM AS PHENATE AND/OR SULF
ONATE

Fraction by Wt: 0.4-0.5%

Other REC Limits:NONE SPECIFIED

=====
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS NOT AVAILABLE

Reports of Carcinogenicity:NTP:UNKNOWN IARC:UNKNOWN OSHA:NO

Health Hazards Acute and Chronic:SKIN: WHILE THIS PRODUCT MAY IRRITATE
THE SKIN FROM PROLONGED SKIN CONTACT, THERE IS NO MEDICAL OR
TOXICOLOGICAL EVIDENCE THAT IT IS AN IRRITANT, A CORROSIVE OR A
CARCINOGEN. IT HAS A LOW ORDER OF ORAL & D
ERMAL TOXICITY.

INHALATION: MIST MAY CAUSE PULMONARY PROBLEMS. IF NOT TREATED, MAY
CAUSE PULMONARY INJURY.

Explanation of Carcinogenicity:BASED UPON AVAILABLE DATA & TECHNOLOGY,
THIS PRODUCT IS NOT CONSIDERED TO BE TOXIC OR CARCINOGENIC TO
HUMANS.

Effects of Overexposure:THE SIGNS AND SYMPTOMS OF OVER-EXPOSURE ARE
UNKNOWN.

Medical Cond Aggravated by Exposure:DIRECT CONTACT WITH THE EYES MAY
CAUSE EYE IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE SKIN
IRRITATION.

=====

=====
First Aid Measures
=====

First Aid:EYES: PURGE EYES WITH COPIOUS AMOUNTS OF WATER. SKIN: CLEANSE WITH WATERLESS SOAP FOLLOWED BY THOROUGH WASHING WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY

=====
Fire Fighting Measures
=====

Flash Point:450F,232C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR MESA/NIOSH APPROVED SELF-CONTAINED

BREATHING APPARATUS. USE WATER SPRAY TO COOL EXPOSED TANKS, DRUMS AND PERSONNEL.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:CONTAIN WITH INERT MATERIAL (FULLERS EARTH, SAND,OIL DRY,ETC.).PREVENT MATERIAL FROM GETTING INTO SEWERS AND OPEN BODIES OF WATER.AREA MAY BE SLIPPERY-PREVENT FALLS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====

=====
Handling and Storage
=====

Handling and Storage Precautions:THESE LUBRICANTS BECOME VERY VISCOUS WHEN STORED AT LOW TEMPERATURES. THEY CONGEAL AT -12 TO -32C. USE PRODUCT WITH CAUTION AROUND OPEN FLAMES, SPARKS

Other Precautions:NONE SPECIFIED BY MANUFACTURER.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE SUPPLIED-AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED.

Ventilation:NONE SP

ECIFIED BY MANUFACTURER.

Protective Gloves:IMPERVIOUS

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:EYE WASH STATION AND SAFETY SHOWER.

INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING AND LAUNDER OR DRY CLEAN BEFORE RE-USE. OIL SOAKED SHOES SHOULD BE DISCARDED.

Supplemental Safety and Health

EMPTY CONTAINER WARNING: CONTAINERS RETAIN RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, B

RASE,
SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME,
SPARK S OR OTHER SOURCES OF IGNITION: THEY MAY EXPLODE AND CAUSE
INJURY. DO NOT ATTEMPT TO CLEAN EMPTY DRUMS.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:600F,316C
Melt/Freeze Pt:M.P/F.P Text:0
Vapor Pres:1
Vapor Density:1
Spec Gravity:1 (WATER=1)
Evaporation Rate & Reference: