

MOBIL OIL CORPORATION -- DELVAC 1330 (SAE 30) -- 9150-00-189-6729  
===== Product Identification =====

Product ID:DELVAC 1330 (SAE 30)  
MSDS Date:01/01/1985  
FSC:9150  
NIIN:00-189-6729  
MSDS Number: BDHSG  
=== Responsible Party ===  
Company Name:MOBIL OIL CORPORATION  
Emergency Phone Num:212-883-4242  
CAGE:1G112

=== Contractor Identification ===  
Company Name:MOBIL CORP  
Address:150 E 42ND ST  
Box:City:NEW YORK  
State:NY  
ZIP:10017-5612  
Country:US  
Phone:212-883-4242  
CAGE:576

35  
Company Name:MOBIL OIL CORPORATION  
Address:3225 GALLOWS RD  
City:FAIRFAX  
State:VA  
ZIP:22037-0001  
Phone:(703) 846-1482  
CAGE:1G112

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')  
CAS:8012-95-1  
RTECS #:PY8030000  
Fraction by Wt: >90%  
OSHA PEL:5 MG/M3  
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVES  
Fraction by Wt: 0.5 LITER(PINT)  
INGEST, IM MED GIVE 1-2 GLASSES OF H\*20. (SEE SUPPDATA)

=====

Fire Fighting Measures =====

Flash Point:425F;218C (OC)  
Extinguishing Media:CO\*2, FOAM, DRY CHEM  
Fire Fighting Procedures:USE NIOSH/MSHA APPRVD SCBA  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,  
DIATOMACEOUS EARTH, OR OTHER ABSORBENT. SHOVEL UP & REMOVE. REPORT  
SPILL TO APPROPRIATE AUTHORITIES. SPILLS THAT MAY REACH WATER(DRY  
CREEKS INCLUDED  
)CALL COAS T GUARD 800-424-8802.

===== Handling and Storage =====

Other Precautions:EYE PROTECTION:IF EYE CONTACT IS LIKELY USE CHEM TYPE  
GOGGLES OR SAFETY GLASSES W/SIDE SHIELDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NEEDED UNDER NORMAL CONDITIONS AND W/  
ADEQUATE VENT(MFR)  
Ventilation:ADEQUATE VENT TO KEEP BELDW TLV.  
Protective Gloves:SEE OTHER EQUIP  
Eye Protection:SEE OTHER PRECAUTIONS  
Othe  
r Protective Equipment:OIL IMPERVIOUS GLOVES FOR RPTD/PRLNG  
EXPOSURE.  
Supplemental Safety and Health  
FIRST AIR PROCEDURE:INGEST-CALL MD/POISON CONTROL FOR WAY TO INDUCE  
VOMIT. IF UNCON-DO NOT INDUCE VOMIT OR GIVE ANYTHING BY MOUTH.  
CONTAINER SIZE:55 GAL DRUM. VP:600F;316C  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:CLEAR LIQUID;MILD ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Stability C

condition to Avoid:STRONG OXIDATION

Hazardous Decomposition Products:METAL OXIDES, CO

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECOMMENDS DILUTING WASTE W/ A FLAMMABLE SOLVENT (FL PT ABOUT 100F) & DISPOSE BY SUPERVISED INCINERATION. DISPOSAL METHOD MUST BE IAW FEDERAL, STATE AND LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.