

ASHLAND OIL, INC -- TECTYL 437,LUBRICANT MIL-C-11796 B, CL3 -- 8030-00-231-2353

===== Product Identification =====

Product ID:TECTYL 437,LUBRICANT MIL-C-11796 B, CL3

MSDS Date:01/01/1985

FSC:8030

NIIN:00-231-2353

MSDS Number: BDKXZ

=== Responsible Party ===

Company Name:ASHLAND OIL, INC

Emergency Phone Num:614-790-3333

CAGE:81355

=== Contractor Identification ===

Company Name:ASHLAND INC

Address:1409 WINCHESTER AVE

Box:391

City:ASHLAND

State:KY

ZIP:41114

Count

ry:US

Phone:800-622-6846

CAGE:81355

Company Name:ASHLAND PETROLEUM CO DIV OF ASHLAND OIL

Address:3855 FISHER RD

Box:28125

City:COLUMBUS

State:OH

ZIP:43216

Country:US

Phone:614-276-5141

CAGE:4N366

===== Composition/Information on Ingredients =====

Ingred Name:2000 PALE OIL (>60%)

ACGIH TLV:5 MG/CUM -MIST

===== Hazards Identification =====

Effects of Overexposure:EYE:SEV IRRIT,RED,TEARNG,BLURRED

VIS.SKIN:PRLNGD/RPTD CONTCT;MOD IRRIT,DEFAT

TNG,DERMTTS.SEE SUP DATA

===== First Aid Measures =====

First Aid:SKIN: WASH THOROUGHLY W/SOAP & WATER. REMOVE CONTAM CLOTHNG.
WASH BFRE REUSE. EYE: IMMED FLUSH W/WATER FOR 15 MIN. INGEST: GIVE
2 GLASSES H*2O, INDUCE VMTNG IMMED W/FINGER. CALL MD. INH: MOVE TO
FRSH AIR. GIVE O*2, ART RESP IF NEC. KP WRM,QUIET, MD.

===== Fire Fighting Measures =====

Flash Point:460F

Fire Fighting Procedures:SELF-CNTND APP W/F

ULL FACPCE OPER IN PRESS

DEMND, POS PRESS

Unusual Fire/Explosion Hazard:WATER OR FOAM MAY FROTH; CAN BE VIOLENT &
ENDANGER LIFE OF FIREFIGHTER!

===== Accidental Release Measures =====

Spill Release Procedures:SM: ABSORB ON PAPER, VERMICULITE, FLOOR
ABSORB, OR OTHER ABSORB MATRL & TRANSFER TO HOOD. LG: MUST WEAR
PROTCTV EQUIP. STOP SPILL AT SOURCE. DIKE, PUMP TO SALVAGE TANK.
REMAIN LIQ, TAKE UP ON SAND, CL AY EARTH, FLOOR ABSORB, ETC. SHOVEL
INTO CNTNRS.

===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS MAY BE HAZ. WHEN EMPTIED
(RETAIN RESIDUE),MUST OBSERVE PRECAUTIONS.

Other Precautions:IF TLV EXCEEDED USE ABOVE MENTIONED RESPIRATOR OR
OTHER NIOSH/MESA APPR. RESPIRATORS,UNDER SPECIFIED
CONDITIONS.OBSERVE OSHA REGULATIONS-SEE YOUR SAFETY EQUIPMENT
SUPPLIER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF

-CNTND BRTHNG APP W/FULL FACPCE OPER IN
PRESS DEMND, POS PRESS

Ventilation:PROVIDE MECH &/OR LOCAL EXH VENTLTN TO KEEP EXPSRE BELOW
TLV

Protective Gloves:BUNA-N,NEOPRENE

Eye Protection:SFTY GLASSES

Other Protective Equipment:PREVENT RPTD/PRLNGD CONTCT. WEAR IMPERVIOUS
BOOTS, CLOTHING

Supplemental Safety and Health

SPEC GRAVITY: < WATER. EXCESS INHAL: NASAL & RESP IRRIT, DIZ, WEAKNSS,
NAUSEA, HDACHE, UNCON, ASPHYXIATN. INGEST: GASTROINT IRRIT, NAUSEA,
VMTNG, DIARRHEA. TLV FOR

PALE OIL PROVIDED BY MFG.

===== Physical/Chemical Properties =====

HCC:N1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:0.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CO, CO*2, VARIOUS HYDROCARBONS, SULFUR
CMPDS, ETC

===== Disposal Considerations =====

Waste Disposal

Methods:SM: ALLOW VOLATILE PORTION TO EVAP IN HOOD.

ALLOW SUFFICIENT TIME FOR VAPOR TO COMPLETELY CLEAR HOOD DUCT WORK.

DESTROY REMAIN BY BURN IRON PAN. LG: DESTROY BY LIQUID INCINERATION
W/OFF GAS SCRUBBER, MFG REC.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be acc
urate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.