

BEESTON, INCORPORATED -- CUTTING FLUID 923 -- 9150-00-231-6699

===== Product Identification =====

Product ID:CUTTING FLUID 923

MSDS Date:01/01/1987

FSC:9150

NIIN:00-231-6699

MSDS Number: BDLCM

=== Responsible Party ===

Company Name:BEESTON, INCORPORATED

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Emergency Phone Num:(207) 883-5541

CAGE:KO732

=== Contractor Identification ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

Stat

e:ME

ZIP:04074

Country:US

Phone:207-883-5541

CAGE:43728

Company Name:BEESTON, INCORPORATED

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

CAGE:KO732

===== Composition/Information on Ingredients =====

Ingred Name:LARD OIL

Fraction by Wt: 100%

===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Health Hazards Acute and Chronic:NONE NOTED.

Effects of Overexposure:NONE NOTED.

Medical Cond Aggravated

by Exposure:NONE NOTED.

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:>440F, >227C
Upper Limits:N.K
Extinguishing Media:CO*2, DRY CHEMICAL, WATER.
Fire Fighting Procedures:NONE NOTED.
Unusual Fire/Explosion Hazard:NONE NOTED.

=====

===== Accidental Release Measures =====

Spill Release Procedures:COVER RESIDUE WITH INERT ABSORBENT MATERIAL
LIKE SAWDUST OR SWEEPING COMPOUND, BRUSH BACK AND FORTH AND SWEEP
UP. AREA OF SPILL MAY BE SLIPPERY AFTER CLEANUP; PROPER PRECAUTIONS
SHOULD BE TAKEN.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY WELL VENTED LOW FIRE
RISK AREA. PROTECT FROM HEAT, SHOCK, FRICTION. KEEP CONTAINERS
CLOSED.
Other Precautions:CLEAN UP RESIDUE THOROUGHLY AS RESIDUE IS SLIPPERY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE
Ventilation:NO SPECIAL REQUIREMENTS W ADEQUATE VENT.
Protective Gloves:AS REQUIRED
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Work Hygienic Practices:WASH AFTER HANDLING.
Supplemental Safety and Health
POUR POINT 45F MAX.

===== Physical/Chemical Properties =====

HCC:V6
Spec G

Gravity:0.912 -0.925
Viscosity:44 CST @ 100F
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LARD OIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
KEEP POROUS MATERIALS SUCH AS RAGS THAT HAVE BEEN SOAKED IN LARD OIL
WELL VENTILATED TO AVOID SPONTANEOUS COMBUSTION.
Stability Condition to Avoid:NONE NOTED.
Hazardous Decomposition Products:NONE NOTED,BUT EXPECT CO, CO*2, H*2O.

===== Disposal Considerations =
=====

Waste Disposal Methods:DISPOSE OF THI WASTE IMMEDIATELY, SINCE THERE IS
SOME POSSIBILITY OF SPONTANEOUS COMBUSTION IF POROUS MTERIAL
SATURATED WITH LARD OIL ARE NOT WELL VENTILATED. DISPOSE OF IN
ACCORDANCE WITH LOCAL, STAT E AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.