

MALLINCKRODT INC.,SCIENCE PRODUCT DIVISION -- ACETONE, CAT #2440 -- 6810-00-234-7208

===== Product Identification =====

Product ID:ACETONE, CAT #2440

MSDS Date:09/05/1985

FSC:6810

NIIN:00-234-7208

MSDS Number: BDLLB

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCT DIVISION

Address:PARIS BYPASS

Box:M

City:PARIS

State:KY

ZIP:40361

Info Phone Num:314-982-5000

Emergency Phone N

um:314-982-5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64-1

RTECS #:AL3150000

Fraction by Wt: 100%

Other REC Limits:NONE

OSHA PEL:1000PPM

ACGIH TLV:750PPM/1000STEL;9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 ORAL RAT=9750MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES:SEVERE

IRRITATION,REDNESS,PAIN;SKIN:IRRITATION,DEFATTING,REDNESS,PAIN,DRYI

NG,CRACKING;IRRITATION TO NOSE,THROAT,MUCOUS

MEMBRANES,DIZZINESS,DULLNESS,HEADACHE,NARCOTIC;INGESTION:NARCOTIC.S

AME SYMPTOMS AS INHALATION. CHRONIC EXPOSURE:PRO

LONGED/REPEATED

SKIN CONTACT MAY PRODUCE SEVERE IRRITATION OR DERMATITIS.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:USE OF ALCOHOLIC BEVERAGES ENHANCES
TOXIC EFFECTS.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED;INGEST:IF

SWALLOWED,GIVE TWO GLASSES OF WATER & INDUCE VOMIT.NOTHING BY MOUTH

IF UNCON;SKIN/EYE EXPOSURE:RMV CONTMNTD CLOTHG.WASH SKIN W/SOAP &

H*2O .FLUSH SKIN/EYES W/LG H*2O;GET MED HELPIIMMEDIATLY

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:0F(-18C)

Autoignition Temp:Autoignition Temp Text:869F

Lower Limits:2.6

Upper Limits:12.8

Extinguishing Media:WATER,DRY CHEM,FOAM,CO*2;WATER SPRAY:TO KEEP EXPD
CANS COOL

Fire Fighting Procedures:USE H*2O TO COOL EXPD CONTRS. USE SCBA & FULL
PROT.CLTHG.

Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE
EXP

LOSIVE WITHIN FLAMMABLE LIMITS; AUTO IGN TEMP:465C(869F)

===== Accidental Release Measures =====

Spill Release Procedures:RMV SOURCES OF IGN.USE PROTCTV

EQUIP/CLOTHG.ISOLATE OR ENCLOSE LEAK/SPILL AREA.ABSORB SM SPILL

W/COMM ABSORBNT &PLACE IN CLOSED CONTNR.DIKE LG SPILL W/DRY SAND OR

EARTH & RECOVER LIQ FOR RECLAMATION W HEN POSSIBLE.SHOVEL ABSORBD

SPILL INTO COVRD DRUM.

===== Handling and Storage =====

Handling a

nd Storage Precautions:KEEP IN TIGHTLY CLOSED
CONTAINERS,STORED IN COOL,DRY,VENTILATED AREA.PROTECT AGAINST
PHYSICAL DAMAGE.ISOLATE FM INCOMPATIBLE MATL,HEAT & SUNLIGHT,ETC.
Other Precautions:AVOID BREATHING VAP.KEEP CONTNR CLOSED.USE W/ADEQ
VENT.DO NOT GET IN EYES,SKIN,OR ON CLOTHING.WASH THOROUGHLY AFTER
HANDLG.KEEP AWAY FM HEAT/FLAME.FOR TRNSFR LIQ,BOND & GROUND
CONTNRS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUPPLIED A
IR RESPIR/SCBA; ESCAPE: GAS MASK
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES/FACE SHIELD
Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE
WASH STATION
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.REMOVE AND
LAUNDER CONTAMINATED CLOTHING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:56.5C(134F)
Melt/Freeze Pt:M.P/F.P Tex
t:-139F(-95C)
Vapor Pres:400 @103F
Vapor Density:2.0
Spec Gravity:0.8
Evaporation Rate & Reference:7.7 (BUTYL ACETATE=1)
Solubility in Water:COMPLETE
Appearance and Odor:CLEAR,COLORLESS,VOLATILE LIQUID.FRAGRANT,MINT-LIKE
ODOR.
Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZERS,CHLOROFORM,ALKALIES,POTASSIUM T-BUTOXIDES,ACIDS.
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous

Decomposition Products:CO, CO*2

===== Disposal Considerations =====

Waste Disposal Methods:LG SPILL & LOT SIZES OF HAZ WASTE CAN BE
ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A
RCRA APPROVED LAND FILL FACILITY.DO NOT FLUSH TO SEWER.ENSURE
COMPLIANCE W/FED,STATE & LOCAL R EGS; REPORTABLE QTY (RQ)
(CWA/CERCLA):5000 LBS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for
use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.