## PRATT AND LAMBERT INC -- 786800 LACQUER C/N GLOSS CLEAR -- 8010-00-251-6495

Product ID:786800 LACQUER C/N GLOSS CLEAR

MSDS Date:01/01/1985

FSC:8010

NIIN:00-251-6495

MSDS Number: BDNVN === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196 === Contractor I dentification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: ISOBUTYL ACETATE

RTECS #:NP9100000 Fraction by Wt: 25% ACGIH TLV:150 PPM

Ingred Name: ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000 Fraction by Wt: 8% OSHA PEL:100 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: TOLUENE (SARA I

II) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 15% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: NAPHTHA ALIPHATIC Fraction by Wt: 15% ACGIH TLV:200 PPM Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN) CAS:8030-30-6 RTECS #:SE7555000 Fraction by Wt: 8%

**OSHA PEL:100 PPM** 

=========== Hazards Identification ==========================

Effects of Overexposure: INHAL: ANEST, IRRIT OF RESPIR TRACT OR ACUT NERV SYS DEPRESN, HDACH, DI ZZ,CONFUS,UNCONSCIOUS, COMA.

First Aid: IN CASE OF CONTCT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING.IF INHALAED. REMOVE TO FRESH AR. CALL A PHYSICIAN IF WYMPTOMS PERSIST.

Flash Point:13 F TCC - 11 C

Lower Limits:.90

Extinguishing Media: USE FIRE EXTING(CO\*2,DRY CHEM OR ALCOH FOAM)LO

FIRE-POLYMER Fire Fighting Proced

ures:SELF-CONTAINED BREATH APPARATUS SHLD BE AVAIL

F/FIREMEN.

Unusual Fire/Explosion Hazard: KEEP CONTNRS TIGHTLY CLOS: ISOLAT FR HEAT, ELECTR EQPMT, SPARKS & OPEN FLAME, CLOS CONTNRS MAY EXPLO(SUP

======== Accidental Release Measures ============

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, & ELECTRICAL, STATIC, OR FRICTIONAL SPARKS) AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

======= Handling and Storage ==============
Handling and Storage Precautions:DO NOT STORE ABOVE 120 F,STORE LG QUANTITIES IN BLDG DESIGNED TO COMPLY W/OSHA 1910.106.  Other Precautions:CONTNRS GROUNDED WHEN POURING.AVD FRE FALL OF LIQD IN EXCES OF FEW INCH.DON'T FLAM CUT,BRAZE OR WELD COATED MATRL W/OBUR OF MINES APPRVD RESPIRAT OR APPROP VENT, ADD LABEL WARM"DO NOT TAKE INT
====== Exposure Controls/Personal Protection ========
Respiratory Protection:O UTDOOR/OPEN AREAS,USE BUR OF MINES APPRVD MECH FILTER RESPIRATOR
Ventilation:PROVDE GEN DILUT OR LOC EXHAUSTVENT IN VOL TO KP BELOW TLV. Protective Gloves:REPEAT CONTACT Eye Protection:SAFETY EYEWEAR.
Other Protective Equipment:PRVNT PROLNG SKIN CONTACT TO CONTAMINATED CLOTHING.
Supplemental Safety and Health UNUS.FIRE & EXPLOS HAZ:WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO VERY HOT SURFACES.
========= Physical/Chemical Properties ==========
HCC:F2 Boiling Pt:B .P. Text:175-290 F Vapor Density:HEAV Evaporation Rate & mp; Reference:SLOWER THAN ETHER Percent Volatiles by Volume:78
========= Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES,HEAT & HOT SURFACES.
======== Disposal Considerations ==========
Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC, STATE & FEDERAL

## OSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to the ir particular situation.