

===== Product Identification =====

Product ID: PENETRATING OIL

MSDS Date: 08/04/1989

FSC: 9150

NIIN: 00-261-7899

MSDS Number: BDPNX

=== Responsible Party ===

Company Name: OMNITECH INTERNATIONAL INC

Address: 800 N ACADIA RD

City: THIBODAUX

State: LA

ZIP: 70301

Country: US

Info Phone Num: 504-446-2003

Emergency Phone Num: 504-446-2003

CAGE: KO342

=== Contractor Identification ===

Company Name: AMERICAN INK AND

OIL CORP

Address: 33 ENDICOTT STREET

Box: City: NORWOOD

State: MA

ZIP: 02062-3006

Country: US

Phone: 781-762-0026 / FAX: 781-762-1617

CAGE: 82956

Company Name: OMNITECH INTERNATIONAL INC

Address: 800 N ACADIA RD

City: THIBODAUX

State: LA

ZIP: 70301

Country: US

Phone: 504-446-2003

CAGE: KO342

Company Name: QPL INC, FORMERLY OMNITECH INTERNATIONAL, INC.

Address: 800 N. ACADIA ROAD

Box: City: THIBODAUX

State: LA

ZIP: 70301

Country: US

Phone: 504-394-8440

CAGE: 0AD61

===== Composition/Information on Ingredients =====

=====

Ingred Name:ALIPHATIC PETROLEUM SOLVENT
CAS:8008-20-6
RTECS #:OA5500000
Other REC Limits:NONE SPECIFIED

Ingred Name:UNIDENTIFIED COMPONENTS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: IRRITATION OF EYES, SKIN,
RESPIRATORY OR G.I. TRACTS; CNS EFFECTS. CHRONIC: DEFATTING OR
DERMATITIS.
Explanation of
Carcinogenicity:DATA PER MSDS
Effects of Overexposure:MAY CAUSE HEADACHE, DIZZINESS, NAUSEA, VOMITING
OR GI TRACT DISTURBANCES POSSIBLE. BURNS OR REDNESS OF
EYES/CRACKING OR DRYNESS OF SKIN.
Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

===== First Aid Measures =====

First Aid:INHALATION:REMOVE TO F
RESH AIR. RESUSCITATE IF NOT BREATHING.
GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.
SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:125F,52C
Extn

guishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:FLOWING PETROLEUM PRODUCTS CAN BE IGNITED
BY STATIC ELECTRICITY.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION; CONTAIN FREE
MATERIAL IF POSSIBLE; USE SUITABLE INERT ABSORBENT MATERIAL AND
RECOVER FOR PROPER DISPOSAL IN AN APPROVED CONTAINER.

Neutralizing Agent:NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL VENTILATED
AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT
CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID
PROLONGED OR REPEATED
BREATHING OF VAPOR. AVOID CONTACT WITH EYES.
USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR AS REQUIRED
IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:NEOPRENE, NITRILE, OR NATURAL RUBBER

Eye Protection:SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment:EYE WASH STAT

ION AND SAFETY SHOWER,WORK
CLOTHING AND APRON AS REQUIRED.

Work Hygienic Practices:OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND
RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR
FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:330F-515F

Melt/Freeze Pt:M.P/F.P Text:-22F,-30C

Vapor P

res: